

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Corner established in 1881 by F.W. Campbell under general land office contract No. 380.

Surveyors general records state:

Set a fir post for corner to sec. 19, 24, 25, & 30

From which:

- A fir 20 ins. dia bears N 28 W, 101ks.
- A fir " " " " N 45 E, 43 lks.
- A fir 6 ins. " " S 23 W, 91ks.
- A tamarack 10ins. dia bears S 35 E 20 lks.



Description of corner evidence found:

No evidence found of fir post as originally set. None of the original bearing trees are found no corolation of trees in the area could be made Heavy logging activity in the area has destroyed all traces of the corner, therefor the position is established by proportion.


Description of monument and accessories I established to perpetuate the original location of this corner:

Set 3"x30" galv iron pipe with 3" brass cap 30" in ground. Stamped brass cap as shown in diagram.

From which:

- A tamarack 11" dia. bears N 13 W 39.7 ft. scribed T8S R31E S12 BT.
- A fir 14" " " N 14 E 11.3 ft. " " R32E S7 "
- A spruce 12" " " S 32-30E 40.7 ft. " " S18 "
- A fir 9" " " S 4 W 31.3 ft. " " R31E S13 "

Nailed brass washers stamped PLS848 & bearing tree signs to each tree, painted red band around each tree. Set steel post with warning sign 5'N from corner Bearing-Solar Grid



Witnesses to above corner  
D. Herburger  
L. Wyllie

Office of.....*Surveyor*..... County of.....*Grant*.....  
 State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office  
 for record on the...*17*... day of...*Jan*....., 19...*81*.....  
 .....*Robert D. Baggett*..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)