


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX R-15

History of original corner establishment:

This corner was originally established by F. W. Campbell under G.L.O. contract number 380, dated March 19, 1881. Survey General notes state:

Set a basalt stone 10x7x6 and dug pits for 1/4 sec. cor.



Description of corner evidence found:

No evidence of this corner is recovered. The search area falls in a cultivated field. Corner believed lost to farming. Set monument at proportionate measure. (See Map of Survey No. 1707)

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the above said proportionate position, Set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 27" in the ground, from which;

Set 5/8"x30" rebar pins w/yellow plastic caps marked "FS&E SURVEY MARKER" as follows:

- N42°15"W, 17.5 ft., no mark on top of pin
- S29°00"E, 20.9 ft., filed 1 groove on top of pin
- S67°15"W, 20.9 ft., filed an X on top of pin

A Juniper 10" dia., bears N79°30'E, 111.00 ft., scribed 1/4 S22 BT

DIAGRAM

T8S R31E
S22
1/4-----
S27
2003
PLS 848

Measurements to accessories taken with a Leica TCA 1100 total station.

I hereby certify that the above corner point was perpetuated as shown hereon on April 4, 2003

Witness: D. Mitchell Ferguson, LSIT
Brad Cates, LSIT

Office of County Surveyor _____ County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office
for record on the 12 day of Aug, 2003
Robert D. Sayre by _____
County Surveyor Deputy

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

RENEWAL DATE:
01/01/2006