


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. V-23

History of original corner establishment:

This corner was originally set by F.W. Campbell under Contract Co. 380 dated March 19, 1881. The notes state that a pine post was set from which:

- A 8" Pine bears S27°W 83 lks (54.8 feet) marked 1/4 S BT
- A 20" Pine bears N28°W 90 lks (59.4 feet) marked 1/4 S BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

No evidence of the original post was found, the corner was re-established from an original BT. From the re-established position:

A 21" Pine bears S27°W 54.8 feet with opened blaze scribed "1/4"

No evidence of the other BT was found.

A North-South fence bears West 28 feet.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 25 inches in the ground and surrounded with a mound of stones to the cap.

Set a steel fence post East of the corner and attached sign 54-4

Established 2 new BT's:

- A 11" Pine bears S3°E 74.5 feet scribed 1/4 S 36 BT
- A 15" Pine bears N7 1/2°W 41.8 feet scribed 1/4 S 36 BT

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.

Attached signs 53-4 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.

Used steel tape and magnetic compass with 19 1/2° east declination . Measured to center of Bts.

See map of survey


This corner set November 7, 1979

- Witnesses:
- D. Kaufman, PLS
 - B. English
 - C. Kelly
 - D. Bartleson

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the 9 day of Jan 1980

Robert W. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)