


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-05

History of original corner establishment:

1884, HERMAN D. GRADON, UNDER CONTRACT NO. 499, ESTABLISHED THE CORNER. HE SET A POST 4' LONG & 4" SQUARE, 24" IN THE GROUND, FROM WHICH:
10" SPRUCE, N. 60° E., 56 LINKS.
8" PINE, S. 36° E., 28 LINKS.
8" PINE, S. 40° W., 24 LINKS.
8" PINE, N. 71° W., 25 LINKS.



Description of corner evidence found:

NONE:

Description of monument and accessories I established to perpetuate the original location of this corner:

FINDING NO EVIDENCE OF THE ORIGINAL CORNER I SET BY DOUBLE PROPORTION A 2 1/2" BY 30" ALUMINUM PIPE, WITH A 3 1/4" ALUMINUM CAP, 21" IN THE GROUND, MARKED AS SHOWN (SEE DIAGRAM), FROM WHICH:

- 7" LODGEPOLE PINE, N. 40 1/4° E., 8.9 FEET, SCRIBED "T8S R34E S8""BT".
- 6" LODGEPOLE PINE, S. 35° E., 9.8 FEET, SCRIBED "T8S R34E S17""BT".
- 10" LODGEPOLE PINE, S. 76° W., 3.5 FEET, SCRIBED "T8S R34E S18""BT".
- 9" LODGEPOLE PINE, N. 41 1/4° W., 14.7 FEET, SCRIBED "T8S R34E S7""BT".

THE BT'S ARE DOUBLE BLAZED AND HAVE A 3/4" BRASS WASHER STAMPED "RLS 2308" NAILED TO THE LOWER BLAZE BETWEEN THE "BT" SCRIBING.

NAD83(1991)

LATITUDE: 44°52'50.93159" NORTH
LONGITUDE: 118°39'25.53348" WEST

MAGNETIC DECLINATION: 20° EAST

WORKED PERFORMED BY: DAVID A. SCHLAICH
WITNESSED BY: RACHELLE (SHELLY) FLETCHER
DATE: AUGUST 30, 1995

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWS 06/30/96

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Oct, 1995
Robert D. Begett by David A. Schlaich
(COUNTY OFFICIAL) (DEPUTY)