

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner has not been previously set.

DIAGRAM
T8S R35 1/2 E

S-N
1/64
S10 | S11

1985
RLS 699

Description of corner evidence found:
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 26" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of earth to be 24" in diameter by 4" high around the monument, from which new BTs are:

7" Lodgepole pine bears S72° 30'W, 37.4' feet scribed S-N1/64 S10 BT

9" Lodgepole pine bears S63°E, 40.7 feet scribed S-N1/64 S11 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet W and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877,
do hereby certify that on June 21, 1985, I established
the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 16 DAY OF OCT, 1985
Robert Q. Baggett, Co. Sur.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1985
LELAND LEE MYERS
699

See MAP OF SURVEY NO. 894