

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

**DIAGRAM**

Corner was established by James H. Hambleton, 645, during subdivision survey dated June, 1968, and an amending survey dated July, 1977.

T8S R35 1/2 E

NW-SW 1/64 No previous monumenting.

S11  
NW-SW  
1/64

Set a one inch iron pipe stamped as per diagram, with a mound of stone around it, being a reference monument which bears S00° 25'E, 8.7 feet from actual corner which is in old road bed. (except year was 1968 and surveyor number was 645).  
Set one bearing tree:

1985  
RLS 699

A lodge pole pine 10" which bears N22°W, 53.15 feet scribed 1/64 S11 BT. No other trees within limits.

**Description of corner evidence found:**

Found reference pipe set by Hambleton bearing S7° 10' 05"W, 9.86' from the computed corner location. As the old road should not have to be used in the future, there was no need for maintaining a reference monument. Therefore, the reference monument was not used and the original bearing and distance to the BT was not checked. Where possible, Hambleton bearing trees were used to reduce the number of scribed trees and the possibility of confusion.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 3/4" aluminum cap, marked as shown in the diagram, 22" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock and earth to be 30" in diameter by 8" high around the monument, from which new BTs are:

6" Lodgepole pine bears N47° 30'E, 54.2 feet scribed NW-SW 1/64 S11 BT.

13" Lodgepole pine bears N30°15'W, 44.6 feet scribed 1/64 S11 BT. (Hambleton BT)

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on June 26, 1985, I established the corner as herein described.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland Lee Myers*

OREGON  
JULY 9, 1963  
LELAND LEE MYERS  
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

*Robert D. Budget, Co. Sur.*

See MAP OF SURVEY NO. 894