

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

History of original corner establishment:  
Corner has not been previously set.

**DIAGRAM**  
T8S R35<sup>1</sup>/<sub>2</sub>E  
S10  
C-W-E  
1/64  
1985  
RLS 699

Description of corner evidence found:  
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3<sup>1</sup>/<sub>4</sub>" aluminum cap, marked as shown in the diagram, 26" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 24" in diameter by 4" high around the monument, from which new BTs are:

5" Lodgepole pine bears S73°W, 29.0 feet scribed X BT

5" Lodgepole pine bears N39° 45'W, 56.5 feet scribed X BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped FLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet S and 25 feet N of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the S post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877,  
do hereby certify that on June 20, 1985, I established  
the corner as herein described.

**FILED**

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

*Robert D. Bayers, Co. Sur.*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland Lee Myers*

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

see MAP OF SURVEY NO. 894