

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was established by W. B. Barr, Deputy Surveyor General, during the original survey Contract No. 492 dated April, 1884.

Set Basalt Stone 16x14x10 ins 10 ins in ground for 1/4 Sec. cor. marked 1/4 on W. face and raised a mound of stone alongside. Trees too small and Pits impracticable

**DIAGRAM**  
T8S R35 1/2 E  
1/4  
S10 | S11  
1983  
RLS 699

Corner was monumented by James H. Hambleton, 645, during a retracement survey dated June, 1968, and an amending survey dated July, 1977.

1/4 cor. 10|11 being a basalt stone 16x14x10 ins., 10 ins. in ground marked 1/4 on W. face and a mound of stone alongside. No trees set. Found mound of stone.

Set a one inch iron pipe with aluminum cap stamped as per diagram (except year was 1968 and surveyor number was 645).

Set two bearing trees:

- A pole pine 12" which bears S56°W, 21.4 feet scribed 1/4 S BT.
- A pole pine 14" which bears N33°E, 59.5 feet scribed 1/4 S BT.

**Description of corner evidence found:**

1" galvanized unflared pipe with 2 1/2" aluminum cap in stone mound. Upon close inspection, found a stone in the mound which was faintly chiseled 1/4. The stone was 16"x14"x10". It appeared that originally the stone was set in the mound, not in the ground. Also there is visible evidence of the mining ditch as called for in the original notes, about 13 feet South from the monument.

- 13" Lodgepole pine (Dead) (Scribing Visible) (1968 BT) bears S56° 45'W, 21.3 feet.
- 15" Lodgepole pine (Dead) (Scribing Visible) (1968 BT) bears N31° 30'E, 60.4 feet.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" galvanized pipe with a 2 1/2" brass cap, marked as shown in the diagram, 24" in the ground, replacing the previous pipe monument in the rock mound. Improved the existing mound with rock to be 30" in diameter by 6" high around the monument, from which new BTs are:

- 18" Englemann spruce bears N16° 45'E, 68.0 feet scribed 1/4 S11 BT
- 16" Lodgepole pine bears S60°W, 96.2 feet scribed 1/4 S10 BT

Sawed off the dead BTs about 6' above the ground. Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4 feet N and 22 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 6, 1983, I re-monumented the corner as herein described.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland Lee Myers*  
OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

**FILED**

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

*Robert D. Baggett, Co. Sur.*

See MAP OF SURVEY NO. 894