

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner was established by James H. Hambleton, 645, during subdivision survey dated June, 1968, and an amending survey dated July, 1977.

**DIAGRAM**

T8S R35 1/2 E

W-E-1/64 11/14 cor. No previous monumenting. Set a one inch iron pipe stamped as per diagram (except year was 1968 and surveyor number was 645). Set two bearing trees:  
A tamarack 14" which bears S17°W, 11.25 feet scribed 1/64 S14 BT.  
A tamarack 12" which bears N39°W, 6.9 feet scribed 1/64 S11 BT.

W-E 1/64  $\frac{S11}{S14}$   
1985  
RLS 699

**Description of corner evidence found:**

Found pipe set by Hambleton bearing N37° 36' 45"W, 11.56' from the computed corner location. Therefore, the corner monument was not accepted and the original bearings and distances to the BTs were not checked. Where possible, Hambleton bearing trees were used to reduce the number of scribed trees and the possibility of confusion.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 3/4" aluminum cap, marked as shown in the diagram, 24" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of earth and rock to be 24" in diameter by 6" high around the monument, from which new BTs are:

- 12" Western larch bears N36° 45'W, 18.3 feet scribed W-E 1/64 S11 BT. (Hambleton BT)
- 15" Western larch bears S87° 45'W, 9.5 feet scribed W-E 1/64 S14 BT.

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet W and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on June 25, 1985, I established the corner as herein described.

**FILED**

IN THE OFFICE OF THE Grant COUNTY SURVEYOR  
THIS 16 DAY OF OCT, 1985

*Robert D. Bayett, Co. Sur.*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland Lee Myers*

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

See MAP OF SURVEY NO. 894