

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by W. B. Barr, Deputy Surveyor General, during the original survey Contract No. 492 dated April, 1884.

Set Granite Stone 15x10x8 ins in ground for cor to Secs. 11, 12, 13, & 14 marked with 1 notch on E and 4 notches on S edges.

from which

- A Pine 12 ins. diam. bears N50°E, (62.7')195 lks. dist. marked T8SR35¹/₂E S12 BT
- A Pine 10 ins. diam. bears S45°E, (21.1')32 lks. dist. marked T8SR35¹/₂E S13 BT
- A Pine 12 ins. diam. bears S70°W, (31.0')47 lks. dist. marked T8SR35¹/₂E S14 BT
- A Pine 43 ins. diam. bears N80°W, (38.3')58 lks. dist. marked T8SR35¹/₂E S11 BT

DIAGRAM

T8S R35¹/₂E

S11	S12
S14	S13

1983
RLS 699

Corner was monumented by James H. Hambleton, 645, during a retracement survey dated June, 1968, and an amending survey dated July, 1977.

Found corner but all bearing trees were dead.

Set a one inch iron pipe with aluminum cap stamped as per diagram (except year was 1968 and surveyor number was 645).

Set three bearing trees. No other tree suitable to scribe.

- A pole pine 10" bears N28°W, 40.8 feet scribed T8SR35¹/₂E S11 BT
- A pole pine 8" bears N11°E, 15.9 feet scribed T8SR35¹/₂E S12 BT
- A douglas fir 24" bears S37°E, 24.25 feet scribed T8SR35¹/₂E S13 BT

Description of corner evidence found:

1" galvanized unflared pipe with 2¹/₂" aluminum cap with original stone alongside.

- 10" Lodgepole pine (3' Stump)(Scribing Visible)(1884 BT) bears S54° 30'E, 22.0 feet
- 12" Lodgepole pine (Dead & Down)(Scribing Visible)(1968 BT) bears N29° 15'W, 40.5 feet
- 9" Lodgepole pine (Dead)(Scribing Visible)(1968 BT) bears N10° 30'E, 14.5 feet.
- 20" Douglas-fir (Good Condition)(Scribing Visible)(1968 BT) bears S35° 45'E, 24.7 feet.
- 12" Pine (1884 BT) not found. 12" Pine (1884 BT) not found. 43" Pine (1884 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3¹/₄" aluminum cap, marked as shown in the diagram, 24" in the ground, replacing the previous pipe monument and burying the stone upside down on the north side of the monument. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument, from which new BTs are:

- 7" Lodgepole pine bears S5° 45'W, 22.7 feet scribed T8SR35¹/₂E S14 BT
- 10" Lodgepole pine bears N63°W, 84.1 feet scribed T8SR35¹/₂E S11 BT
- 10" Lodgepole pine bears N12° 30' E, 25.5 feet scribed T8SR35¹/₂E S12 BT

Sawed off the dead BT about 6' above the ground. Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 13, 1983, I re-monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1983

Robert H. Bayne Co. Sur.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

See MAP OF SURVEY NO. 894