


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by W. B. Barr under GLO contract number 492, dated August 22, 1883. Surveyor General record states: Set a spruce stake 4' long 4' square for the 1/4 cor. from which;

A Tamarack 24 ins. diam bears N 30 E, 57 lks dist. marked 1/4 SBT.
A Pine 8 ins. diam. bears S 80 W 27 lks dist. marked 1/4 SBT



No record of subsequent monumentation found in Grant County survey records.

Description of corner evidence found:

Found a 18" Tamarack N 17 E, 57 lks scribes visible. Dead snag.
Found a 9" Pine S 70 W, 27 lks scribes visible, dead & down.

Description of monument and accessories I established to perpetuate the

original location of this corner: At the intersection of record distances from the bearing trees, I set a 2 1/2" X 30" aluminum pipe with aluminum cap marked as shown, 30" in the ground, from which;

New Bearing Trees

- A 8" White Fir bears N 17° E, 3.73 ft. marked 1/4 S 15 BT.
- A 6" White Fir bears S 20° E, 5.21 ft. marked X BT.
- A 9" Spruce bears S 41° W, 24.23 ft. marked 1/4 S 22 BT.
- A 6" White Fir bears N 88 W, 17.60 ft. marked F BT.

Set a steel fencepost approximately 5 feet West, with signs attached.

I hereby certify that the above corner point was perpetuated as hereon described on July 31, 1990.


Witness: Jeff Petersen
Jim Bennett

T8S R35 1/2 E

S 15

1/4 ———
S 22

1990
OPLS 644



I used a steel tape and magnetic compass in the establishment of new accessories. I used 19° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of... Surveyor County of... Grant

State of... Oregon I hereby certify that the within instrument was filed in this office for record on the... 27 day of... Sept , 1990

Robert D. Griffith by
(COUNTY OFFICIAL) (DEPUTY)