


T-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None



Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

At CORNER POSITION determined by survey set a 2 1/2"x30" galv. iron pipe with brass cap 26" in ground with raised mound of stone marked:

From which:

A Pond. Pine 12" dia. bears S79°E 77.4 ft. marked C1/4 S27 BT.

A Pond. Pine 16" dia. bears S77°W 21.8 ft. marked C1/4 S27 BT.

T8S R35E

C1/4 | S27

PLS 1099  
1983

Attached brass washers stamped LS 1099 to BT blaze on both trees.

Corner location perpetuated in accord. with Umatilla N.F. Survey Contract No. 53-04R3-2-01275.

20°E Declination  
Steel Tape

Post 5'± North w/54-9

August 31, 1983

Witnesses: A. Ray Crapo  
Greg Orton  
Kyle McKinney

Corner falls 50'± below old logging road on open south face on steep hill

Refer to Grant County Survey No. 828

Office of.....SURVEYOR..... County of.....GRANT.....

State of.....OREGON....., I hereby certify that the within instrument was filed in this office for record on the.....30..... day of.....AUG....., 19.....84.....

.....Robert O. Degeat..... by.....[Signature].....  
(COUNTY OFFICIAL) (DEPUTY)

