

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

(Corner history continued)

Attached brass cap stamped: (marked as shown in corner diagram)


From which:

A Lodge Pole Pine 14" dia. bears N 85°W 41.6 ft. scribed T8S R35E S27 BT.

A Lodge Pole Pine 8" dia. bears N 50°E 73.9 ft. scribed T8S R35E S26 BT.

A Lodge Pole Pine 6" dia. bears S 78½°E 75.3 ft. scribed T8S R35E S35 BT.

A Lodge Pole Pine 6" dia. bears S83°W 70.3 ft. scribed T8S R35E S34 BT. Attached brass washers stamped LS 1099 to foot blaze of all BT's.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 24, 1917
WILLIAM R. WELLS
1106

Renews 6/30/98

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 18 day of Dec, 1996
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)