

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X-21

History of original corner establishment:

1884, Herman D. Gradon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 499, set a post 3 ft. long, 3 ins. square, 24 ins. in the ground for 1/4 sec. cor., from which:

A pine 6 ins. dia. brs. N 32° E, 52 lks. dist. marked 1/4SBT  
A pine 10 ins. dia. brs. S 10° W, 37 lks. dist. marked 1/4SBT.

1921, C.W. Waterbury, of Baker Ranger District of Whitman N.F., found Bearing tree - Lodgepole pine, 8" diameter, bearing S10°W, distance 37 links. Bearing tree cut off above witness. Snag rotting loose. and he Rewitnessed 6" L.P. 1 foot distance from original bearing tree. (Forest Service Corner Card on file at Umatilla N.F.)

1982, Gary L. Langlitz, Registered Land Surveyor 1099, found the original southwest BT and Waterbury's BT, and at a position N10°E 24.4 ft. (record) from original BT set a 2 1/2" X 30" Galvanized Iron Pipe, 24" in ground with mound of stone and dirt to top of pipe with brass cap attached (Grant Co. Map of Survey No. 828), from which:

The Original BT - A down Lodgepole Pine 10" dia., bears S10°W 24.4 ft. with visible scribing 1/4S BT.

Unrecorded BT - A Lodgepole Pine 10" dia., bears S11°W 25.0 ft. dead with visible scribing "1/4 S FS BT" (Waterbury's BT).

New BT's - A Lodgepole Pine 9" dia., bears N77 1/2°W 48.6 ft. scribed 1/4 S35 BT.  
A Lodgepole Pine 9" dia. bears N11 1/2°E 57.7 ft. scribed 1/4 S36 BT.

1998, Robert D. Bagett, Registered Land Surveyor 598, found a 2 1/2" Galvanized Iron Pipe with attached Brass Cap (Grant Co. Map of Survey No. 1489), from which:  
A dead and down fir 8" dia. bears S.12°W. 24.4 ft. with scribing visible.

A Lodgepole Pine 9" dia. bears N.11 1/2°E. 57.7 ft. marked 1/4 S36 BT.

A Lodgepole Pine 9" dia. bears N.77 1/2°W. 48.0 ft. marked 1/4 S35 BT.

SCRIBE NEW BEARING TREES:

A Lodgepole Pine 8" dia. bears S.50°E., 27.0 ft. marked 1/4 S36 CSBT.

A Lodgepole Pine 10" dia. bears S.14°W., 39.6 ft. marked 1/4 S35 CSBT.

Description of corner evidence found:

Found a 2 1/2" iron pipe, with a 2 1/2" brass cap, projecting 5" out of the ground, marked as shown, from which:

10" Lodgepole Pine, N 10° E, 57.7 feet with scribing "1/4 S36" "BT" visible on a partially healed double blaze and 1 1/4" brass washer stamped "LS 1099" nailed to lower blaze.

8" Lodgepole Pine, S 54 1/2° E, 27.0 feet with scribing "1/4 S36" "CSBT" visible on double blaze.

10" Lodgepole Pine, S 11 3/4° W, 69.7 feet with scribing "1/4 S35" "CSBT" visible on double blaze.



9" Lodgepole Pine, N 79 1/2° W, 48.0 feet with scribing "1/4 S35" "BT" visible on partially healed double blaze and 1 1/4" brass washer stamped "LS 1099" nailed to lower blaze.

Remains of a downed snag with scribing visible at indeterminate bearing and distance (believed to be original S 10° W, 37 links BT).

Description of monument and accessories established to perpetuate the original location of this corner:

None

DIAGRAM



REGISTERED PROFESSIONAL LAND SURVEYOR

David A. Schlaich

OREGON JULY 16, 1987 DAVID A. SCHLAICH 2308

RENEWAL DATE: 06/30/2000

Magnetic Declination 19° East  
WORK PERFORMED BY: David A. Schlaich (RLS 2308)  
DATE: October 27, 1999

Office of... Surveyor ..... County of... Grant .....  
State of... Oregon ....., I hereby certify that the within instrument was filed in this office  
for record on the... 9 day of... Feb ..... 19... 2000 .....  
Robert D. Bagett ..... by.....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SEE MAP OF SURVEY NO. 1543

X-21