


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-17

History of original corner establishment:

This corner was originally established by Otis Gould, U.S. Cadastral Surveyor, under special instructions dated Nov. 25, 1935, during his surveys in July through October, 1937. The original notes state that at the corner a marked brass cap on a 2" by 3' long iron post was set 20" in the ground to bedrock, and in a mound of stone to top from which:



- A pine, 10" diam., bears N.19¹/₂^oE., 10 lks. dist., marked T8S, R36E, S11 BT.
- A pine, 10" diam., bears S.57¹/₂^oE., 9 lks. dist., marked T8S, R36E, S14 BT.
- A pine, 12" diam., bears S.22^oW., 8 lks. dist., marked T8S, R36E, S15 BT.
- A pine, 10" diam., bears N.39¹/₂^oW., 16 lks. dist., marked T8S, R36E, S10 BT.

Description of corner evidence found:

A 2¹/₂" brass cap on 2" flanged galvanized iron pipe protruding 20" from ground and 12" from a mound of stone from which:

- A 12" lodgepole pine bears N.33^oE-6.9' with scribing visible on open blaze.
- A 10" dead standing lodgepole pine bears S.60^oE-6.9' with scribing visible on open blaze.
- A 10" dead standing lodgepole pine bears S8^oW-5.3' with scribing visible on open blaze.
- A 8" dead down lodgepole pine bears N30^oW-10.6' with scribing visible on open blaze.

The corner is located 250' East of a N-S creek on East sloping ground. Walk to corner from 1/4 S10 S15

Description of monument and accessories established to perpetuate the original location of this corner:


Maintained monument by building a mound of stone around it. From the monument:

- A 9" alpine fir bears S33^oE-4.4', scribed T8S, R36E, S14 BT.
- A 12" englemann spruce bears S33^oW-34.9', scribed T8S, R36E, S15 BT.
- A 10" englemann spruce bears N 18¹/₂^oW-27.0', scribed T8S, R36E, S10 BT.

New bearing trees have a brass washer stamped PLS 1106 nailed to the face of blaze. Attached sign 54-3 and 54-9 and painted face of blaze and a 6" red band around each bearing tree. Set steel fence post North of corner and attached sign 54-9.

Used steel tape and staff compass with 19^o E declination, measured to the center of the bearing trees.

The cap is a standard GLO brass cap marked:



This corner was maintained on July 23, 1986.

Witness: Willard Hulick

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

William R. Wells

**OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106**

Office of... County Surveyor County of... Grant
 State of... Oregon I hereby certify that the within instrument was filed in this office
 for record on the... 8... day of... Sept 19... 86
Robert D. Baggett by
 (COUNTY OFFICIAL) (DEPUTY)