

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-15

History of original corner establishment:

Original corner established by Herman D. Gradon on June 21, 1884, under contract No. 499, as follows:

Set a post, from which:

- A 10" Pine bears N58°W, 17 links (11.22 feet).
- A 7" Spruce bears S53°W, 8 links (5.28 feet).

DIAGRAM

T9S R34E
1/4 S22
S27
PLS 1636
1993

Description of corner evidence found:

The original post is gone.

- A 9" Lodgepole Pine with full scribes visible bears N58°W, 11.22 feet.
- A 12" Englemann Spruce with healed double blazes bears S53°W, 5.28 feet.

Description of monument and accessories established to perpetuate the original location of this corner:

At the intersection of record bearing and distance from the original bearing trees, set a 2 1/2" by 30" aluminum pipe 30" into the ground with a small mound of stones around the pipe. A 3 1/4" aluminum cap attached is marked as shown in the diagram above. From which:

- A 18" Western Larch scribed "1/4 S22 BT" bears N89°30' E, 25.7 feet.
- A 16" Western Larch scribed "1/4 S27 BT" bears S28°E, 37.0 feet.

The new bearing trees are scribed on double blazes. The new bearing trees and the Lodgepole Pine have a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower blaze. All 4 bearing trees have a 54-3, Bearing Tree sign nailed above the blazes and a 54-9, Land Survey Monument sign nailed to the back.

I hereby certify the above corner point was perpetuated as hereon described on September 15, 1993.

Magnetic Declination: 20°E.

NAD1983 Geographic Position (+ or - 2 to 6 meters)

Latitude 44-45-51.868 N

Longitude 118-36-21.864 W

Witnessed by: Troy Allen

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Dennis L. Gaylord

OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

EXPIRES 12-31-93

Office of Surveyor County of GRANT
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 15th day of OCT, 1993
Troy Allen by Dennis L. Gaylord
(COUNTY OFFICIAL) (DEPUTY)