

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-13

History of original corner establishment:

Original corner established by Herman D. Gradon on June 19, 1884, under contract No. 499, as follows:

Set a granite stone 14"x 8"x 8", 10" into the ground marked with 1 notch on the south and 3 notches on the east edges, from which:

- A 9" Fir bears S28°W, 17 links (11.22 feet).
- A 10" Spruce bears N28°E, 19 links (12.54 feet).
- A 12" Spruce bears S48°E, 21 links (13.86 feet).
- A 14" Spruce bears N60°W, 28 links (18.48 feet).

DIAGRAM

T9S R34E	
S28	S27
S33	S34
PLS 1636	
1993	

Description of corner evidence found:

The original stone is a solidly set granite stone 14"x 8"x 8" marked with 1 notch on the south and 3 notches on the east edges, from which:

- A 23" Englemann Spruce with scribes visible on a nearly healed blaze bears N56°W, 17.7 feet.
- The original Fir is down and decayed. Full scribes are visible. Root hole bears S21°W, 10.5 feet.
- A root hole bears N28°E, 12.54 feet.
- A root hole bears S48°E, 13.86 feet.

Description of monument and accessories | established to perpetuate the original location of this corner:

In place of the original corner stone, set a 2 1/2" by 30" aluminum pipe 20" into the ground in a mound of stones to the top of the pipe. A 3 1/4" aluminum cap attached is marked as shown in the diagram above. The corner stone is buried along the east side of the pipe. From which:

- A 20" Englemann Spruce scribed "T9S R34E S27 BT" bears N46°E, 25.7 feet.
- A 21" Englemann Spruce scribed "T9S R34E S34 BT" bears S78°30'E, 23.4 feet.
- A 25" Englemann Spruce scribed "T9S R34E S33 BT" bears S28°30'W, 22.3 feet.

The new bearing trees have a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower of two blazes. All 4 bearing trees have a 54-3, Bearing Tree sign nailed above the blazes and a 54-9 Land Survey Monument sign nailed to the back of the tree.

I hereby certify the above corner position was perpetuated as hereon described on September 15, 1993.

Magnetic Declination: 20° E.

NAD1983 Geographic Position (+ or - 2 to 6 meters):

Latitude 44-44-59.326 N

Longitude 118-36-57.803 W

Witnessed by: Troy Allen

Office of Surveyor County of GRANT

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the 15 day of OCT, 1993

Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Dennis L. Gaylord
OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

EXPIRES 12-31-93