

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


N - 13

History of original corner establishment:

Corner originally established on June 20, 1884 by Herman D. Gradon under GLO contract no. 499 as follows:

Set post for corner from which:

- A 8" Pine bears N68°E, 27 links (17.82 feet).
- A 8" Fir bears S32°E, 15 links (9.90 feet).
- A 10" Pine bears S32°W, 24 links (15.84 feet).
- A 8" Fir bears N62°W, 24 links (15.84 feet).



Description of corner evidence found:

The original post is gone.

The original 10" Pine is a 10" Lodgepole Pine snag with full scribing visible on double blazes. Bears S35°W, 15.84 feet.

The original 8" Pine is a down 6" Lodgepole Pine with full scribes visible. Root crown bears N71°E, 17.82 feet.

The original 8" Fir is a 11" White Fir snag 15' high with full scribes visible on partly healed double blazes. Bears N60°W, 15.84 feet.

The original 8" Fir is a down and decayed White Fir with some scribes visible on nearly healed blazes. Root crown bears S32°E, 9.90 feet.

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point as determined by reference to the original bearing trees, set a 2 1/2" x 30" aluminum pipe 27" into the ground. A 3 1/4" aluminum cap attached is marked as shown in the diagram above, from which:

- A 9" White Fir scribed "T9S R34E S16 BT" bears N23°W, 7.0 feet.
- A 21" Western Larch scribed "T9S R34E S15 BT" bears N38°E, 3.1 feet.
- A 23" Western Larch scribed "T9S R34E S22 BT" bears S79°E, 31.6 feet.
- A 20" Western Larch scribed "T9S R34E S21 BT" bears S35°W, 28.2 Feet.

All four new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower blaze. All bearing trees and bearing tree remnants have a 54-3, Bearing Tree, sign nailed above the blazes. A 54-9, Land Survey Monument, sign is nailed to the back of the six standing bearing trees.

I hereby certify the above corner point was perpetuated as hereon described on October 6, 1994. Magnetic Delination: 20°E.

NAD1983 Geographic Position (+ or - 2 to 5 meters):
Latitude 44-46-43.87 N
Longitude 118-36-58.07 W

REGISTERED PROFESSIONAL LAND SURVEYOR

Dennis L. Gaylord

OREGON
JULY 14, 1968
DENNIS L. GAYLORD
1636

Office of COUNTY SURVEYOR County of GRANT
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 30 day of JUNE, 1995
Robert D. Degett by _____
 (COUNTY OFFICIAL) (DEPUTY)

Revised 6/30/95