

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-13

History of original corner establishment:

Original corner established by Herman D. Gradon on June 19, 1884, under contract No. 499, as follows:

Set a granite stone 14"x 8"x 8", 10" into the ground marked with 1 notch on the south and 3 notches on the east edges, from which:

- A 9" Fir bears S28°W, 17 links (11.22 feet).
- A 10" Spruce bears N28°E, 19 links (12.54 feet).
- A 12" Spruce bears S48°E, 21 links (13.86 feet).
- A 14" Spruce bears N60°W, 28 links (18.48 feet).

DIAGRAM

T9S	R34E
S28	S27
S33	S34
PLS 1636	
1993	

Description of corner evidence found:

The original stone is a solidly set granite stone 14"x 8"x 8" marked with 1 notch on the south and 3 notches on the east edges, from which:

- A 23" Englemann Spruce with scribes visible on a nearly healed blaze bears N56°W, 17.7 feet.
- The original Fir is down and decayed. Full scribes are visible. Root hole bears S21°W, 10.5 feet.
- A root hole bears N28°E, 12.54 feet.
- A root hole bears S48°E, 13.86 feet.

Description of monument and accessories | established to perpetuate the original location of this corner:

In place of the original corner stone, set a 2 1/2" by 30" aluminum pipe 20" into the ground in a mound of stones to the top of the pipe. A 3 1/4" aluminum cap attached is marked as shown in the diagram above. The corner stone is buried along the east side of the pipe. From which:

- A 20" Englemann Spruce scribed "T9S R34E S27 BT" bears N46°E, 25.7 feet.
- A 21" Englemann Spruce scribed "T9S R34E S34 BT" bears S78°30'E, 23.4 feet.
- A 25" Englemann Spruce scribed "T9S R34E S33 BT" bears S28°30'W, 22.3 feet.

The new bearing trees have a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower of two blazes. All 4 bearing trees have a 54-3, Bearing Tree sign nailed above the blazes and a 54-9 Land Survey Monument sign nailed to the back of the tree.

I hereby certify the above corner position was perpetuated as hereon described on September 15, 1993.

Magnetic Declination: 20° E.

NAD1983 Geographic Position (+ or - 2 to 6 meters):
Latitude 44-44-59.326 N
Longitude 118-36-57.803 W

Witnessed by: Troy Allen

Office of Surveyor County of GRANT

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the 15th day of OCT, 1993

Robert D. Bayliff by (COUNTY OFFICIAL) (DEPUTY)

REGISTERED PROFESSIONAL LAND SURVEYOR

Dennis L. Gaylord

OREGON JULY 14, 1978 DENNIS L. GAYLORD 1636

EXPIRES 12-31-93