

**REGISTERED PROFESSIONAL LAND SURVEYOR**  
**WILLIAM L. HANLEY**  
 JULY 14, 1978  
 OREGON  
 1639

*William L. Hanley*

(DEPUTY)

(COUNTY OFFICIAL)

by

1979

for record on the day of


I hereby certify that the within instrument was filed in this office

Office of County Surveyor, County of Grant, Oregon

I hereby certify the above corner was properly established on June 13, 1979 witnessed by Tracy Labarge and Tom Fisk.

New bearing trees:  
 A pine 6 ins diam bears N 14° W, 37.8 ft dist mkd N 1/16 S 1 BT  
 A pine 8 ins diam bears S 81° W, 46.7 ft dist mkd N 1/16 S 1 BT  
 Each BT has a sign 54-5 attached below a band of red paint and has a brass washer marked LS 1639 nailed flush with BT blaze.

1979 OILS 1639



Brass cap marked thus:  
 Set a 2 1/2 inch brass cap on 2 inch iron pipe 31 ins long, 26 ins in the ground with a 6 ft steel fence post along side with a sign 54-9 attached.

Description of monument and accessories | established to perpetuate the original location of this corner:

None

Description of corner evidence found:

*None*  
~~Witnessed by revised return sheet filed 8/2/79~~  
 OK

None: Corner established this survey.

History of original corner establishment:

