

C-23

(DEPUTY)

(COUNTY OFFICIAL)

Robert D. [Signature]
by

for record on the 13 day of July, 1979

State of Oregon, I hereby certify that the within instrument was filed in this office

Office of County Surveyor, County of Grant

1639
WILLIAM L. HANLEY
JULY 14, 1978
OREGON

William L. Hanley

REGISTERED
PROFESSIONAL
LAND SURVEYOR

I hereby certify that the above monument was established as herein described on June 14, 1979 witnessed by Tracy Labaree.

Each BT has a sign 54-5 attached below a band of red paint and a brass washer marked LS 1639 nailed flush with BT blaze.

A pine 10 ins diam bears N 29° E, 61.8 ft dist mkd C 1/4 S 1 BT
A pine 6 ins diam bears N 27° W, 87.9 ft dist mkd C 1/4 S 1 BT

New bearing trees:

ORLS 1639

1979

C 1/4 S 1

Brass cap marked thus: T 9 S R 35 E

Set a 2 1/2 inch brass cap on a 2 inch iron pipe 31 ins long, 3 inches in ground with a 6 ft steel fence post along side with a sign 54-9 attached.

original location of this corner:

Description of monument and accessories | established to perpetuate the

~~Supervised by [Signature] filed 8/2/79 OK~~

[Signature]

None

Description of corner evidence found:

None: Corner established this survey.

History of original corner establishment:

