


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Herman D. Gradon under GLO Contract No. 499 dated March 11, 1884.



Surveyor General's records state:

Set a post 3 ft long 3 ins square 24 ins in the ground for 1/4 sec cor marked 1/4 S on W face, from which:

- A pine 10 ins diam bears S 54° W, 36 lks dist mkd 1/4 S BT
- A pine 07 ins diam bears N 11° W, 58 lks dist mkd 1/4 S BT

Description of corner evidence found:


A dead pine 12 ins diam for NW BT with full scribes on open blaze.

At the record bearing and distance I found an aluminum cap on a 1 inch iron pipe marked 1/4 S 1 |.

Description of monument and accessories I established to perpetuate the original location of this corner:

As per advisory letter No. 9641.5 (942) from the Chief, Branch of Cadastral Survey, Oregon State Office, B.L.M. and the 1973 Manual of Survey Instructions Sec 5-35 (paragraph 3) and Sec 5-41 (paragraph 3) I set a 2½ inch brass cap on a 2 inch iron pipe 31 ins long, 28 ins in the ground with a 6 ft steel fence post alongside with signs 54-2 and 54-4 attached. This monument is re-established at the intersection of a line E from the found monument with the W line of the NW1/4 sec 4 T 9 S R 35½ E, W.M.

Brass cap marked thus:



New bearing trees:

- A pine 6 ins diam bears S 59° W, 35.6 ft dist mkd 1/4 S 1 BT
- A pine 6 ins diam bears S 38° W, 25.5 ft dist mkd X BT

Each BT has a sign 54-3 attached below a band of red paint and has a brass washer marked LS 1639 nailed flush with BT blaze.

I hereby certify the above corner was properly re-established on June 13, 1979 witnessed by Tracy Labaree and Tom Fisk.

REGISTERED PROFESSIONAL LAND SURVEYOR

William L. Hanley

OREGON JULY 14, 1978 WILLIAM L. HANLEY 1639
--

Office of... County Surveyor County of... Grant

State of... Oregon I hereby certify that the within instrument was filed in this office

for record on the... 2nd day of... August 1977.

Robert D. Baggett by (COUNTY OFFICIAL) (DEPUTY)