


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G-13

History of original corner establishment:

Herman D. Gradom under G.L.O. contract number 499, dated Mar. 11, 1884, set a basalt stone 18"X 10"X 6" twelve inches in the ground. He marked "1/4" on the west face of the stone. From the corner:

- A Fir, 7" dia., S40°E, 48 lks.
- A Pine, 20" dia., S50°W, 15 lks.



Description of corner evidence found:

At the corner point, established at record distance from the original BTs, I found scattered fragments of stone with no marks evident. From the corner:

- A Douglas Fir, 20" dia., S40°E, 31.7 ft., with a healed blaze.
- A Ponderosa Pine, 21" dia., S50°W, 9.9 ft., with scribing visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2"X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I buried the original stone fragments alongside and built a stone mound around the monument.

T9S R35E
1/4
S9 | S10
PLS 1832
1986

The original BTs have the blaze and a 6" band painted red, BT tags and "Attention" signs. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18 1/2° E.

Oct. 13, 1986

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 15 day of Dec, 1986
Robert D. Gage by _____
 (COUNTY OFFICIAL) (DEPUTY)