

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-17

History of original corner establishment:

1884, Herman D. Graddon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 499 established this corner. He set a post 4' long, 4" square, 24" in the ground, from which:
8" Spruce, N 87° E, 37 links.
12" Pine, S 52° E, 27 links.
12" Pine, S 4° W, 52 links.
12" Spruce, N 39° W, 74 links.

1901 - 1905, The corner was found and tied by Mineral Surveys 400 and 601.

1982, Harry C. Hildebrand, Registered Land Surveyor 1898, found the SW BT and set at record bearing and distance, a 2 1/2" by 32" steel pipe, with brass cap, 22" in the ground with a mound of stone, from which:
Down and rotted Pine, S 4 W, 34.3 feet, marked "T9S R35E S15 BT".

Marked New BT's:
16" Ponderosa Pine, N 27° E, 46.0 feet.
5" Lodgepole Pine, S 69°30' E, 24.56 feet.
11" White Fir, S 12° W, 59.90 feet.

1997, David A. Schlich, Registered Land surveyor 2308, found a 2 1/2" iron pipe, with a 2 1/2" brass cap, projecting 11" out of a mound of stone (Grant Co. Map of Survey No. 1454), from which:


17" Lodgepole Pine, N 25 1/4° E, 46.0 feet, scribing visible on partially healed blaze, with nail on west side of the tree with 1 1/4" washer marked "LS 1898".
8" Lodgepole Pine, S 69 1/2° E, 23.4 feet, marked with "X" at 4' height and "BT" on low blaze, with nail on north side of the tree with 1 1/4" washer marked "LS 1898".
13" Englemann Spruce, S 10° W, 59.9 feet, scribing visible on single blaze, with nail on west side of the tree with 1 1/4" washer marked "LS 1898".
Marked New BT:
8" Ponderosa Pine, N 83° W, 46.1 feet.

1998, Douglas M. Ferguson, Registered Land Surveyor 848, found and tied the corner while performing a R-O-W Survey for Grant County (Grant Co. Map of Survey No. 1463).

Description of corner evidence found:

Found a 2 1/2" iron pipe, with a 2 1/2" brass cap, projecting 11" out of the ground, surrounded by a ring of stones, marked as shown, from which:

17" Lodgepole Pine, N 25 1/4° E, 46.0 feet, with scribing visible on partially healed blaze, and 1 1/4" brass washer stamped "LS 1898" nailed to west side of the tree.
8" Lodgepole Pine, S 69 1/2° E, 23.4 feet, with scribed "X" at a height of 4 feet with "BT" on low blaze, and 1 1/4" brass washer stamped "LS 1898" nailed to north side of the tree.
13" Englemann Spruce, S 10° W, 59.9 feet, with scribing visible on a single blaze and 1 1/4" brass washer stamped "LS 1898" nailed to west side of the tree.
8" Ponderosa Pine, N 83° W, 46.1 feet, with scribing "T9S R35E S10" "BT" visible on a double blaze and 3/4" brass washer stamped "RLS 2308" nailed to the lower blaze.



Description of monument and accessories I established to perpetuate the original location of this corner:

New Reference:
5/8" rebar, with a 1 1/2" aluminum cap, stamped "GCRW 23+50 30.00 RT", S 53°31' W, 121.67 feet.

Magnetic Declination 19° East

WORK PERFORMED BY: David A. Schlaich (RLS 2308)
DATE: September, 1999

REGISTERED PROFESSIONAL LAND SURVEYOR

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWAL DATE: 06/30/2000

Office of... SURVEYOR County of... GRANT
State of... OREGON, I hereby certify that the within instrument was filed in this office
for record on the... 3 day of... NOV, 19... 99
Robert D. Smith by.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SEE MAP OF SURVEY NO. 1534

J-17