

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

R-13

History of original corner establishment:

1884, HERMAN D. GRADON, U.S. DEPUTY SURVEYER, ESTABLISHED THE CORNER WHILE WORKING UNDER G.L.O. CONTRACT NO. 499. HE SET A POST 4' BY 4" SQUARE, 24" IN THE GROUND FOR THE CORNER, FROM WHICH:


- 6" PINE BEARS N 70° E, 35 LINKS.
- 14" FIR BEARS S 63° E, 64 LINKS.
- 9" FIR BEARS S 60° W, 52 LINKS.
- 8" PINE BEARS N 52° W, 38 LINKS.

1968, JAMES H. HAMBLETON, REGISTERED LAND SURVEYOR NO. 645, FOUND THE NW (DEAD) & SE (ALIVE) BEARING TREES AND SET A 1" IRON PIPE WITH CAP FOR THE CORNER, MARKED NEW BT'S:

- 6" FIR BEARS N 42° W, 11.2 FEET.
- 15" FIR BEARS N 34° E, 16.2 FEET.

1982, JAMES W. PROCHNAU, REGISTERED LAND SURVEYOR NO. 1305, FOUND A 2 1/2" ALUMINUM CAP IN A 1" IRON PIPE, FROM WHICH:

- 20" DOUGLAS FIR BEARS S 63° E, 42.4 FEET (ORIGINAL BT).
- 13" DOUGLAS FIR (DEAD & DOWN) BEARS S 60° W, 34.3 FEET (ORIGINAL BT).
- 7" DOUGLAS FIR BEARS N 42° W, 11.2 FEET.
- 16" DOUGLAS FIR BEARS N 30° E, 16.6 FEET.
- MARKED NEW BT:
- 9" LARCH BEARS S 5° W, 55.1 FEET, SCRIBED "T9S R35E S28 BT".



Description of corner evidence found:

FOUND A 1 1/4" IRON PIPE, WITH A 2 1/2" ALUMINUM CAP, PROJECTING 8" OUT OF THE GROUND, MARKED AS SHOWN (SEE DIAGRAM), FROM WHICH:

- 17" DOUGLAS FIR, BEARS N 33 1/4° E, 16.1 FEET, SCRIBING "T9S R35E S22" "BT" VISIBLE ON A PARTIALLY HEALED DOUBLE BLAZE.
- 20" DOUGLAS FIR BEARS S 63 1/2° E, 43.2 FEET, SCRIBING "T9" VISIBLE ON A SINGLE BLAZE.
- 10" WESTERN LARCH BEARS S 5° W, 55.1 FEET, SCRIBING VISIBLE ON PARTIALLY HEALED UPPER BLAZE AND COMPLETELY HEALED LOWER BLAZE.
- 10" DOWNED DOUGLAS FIR SNAG (S 60° W, 52 LINKS), SCRIBING VISIBLE ON SINGLE BLAZE.
- 7" DOUGLAS FIR SNAG BEARS N 43° W, 11.2 FEET, SCRIBING "T9S R35E S21" "BT" ON DOUBLE BLAZE.

Description of monument and accessories established to perpetuate the original location of this corner:

MARKED NEW BT:
7" LODGEPOLE PINE BEARS N 8° W, 35.7 FEET, SCRIBED "T9S R35E S21" "BT" ON DOUBLE BLAZE, WITH A 3/4" BRASS WASHER STAMPED "RLS 2308" NAILED TO THE LOWER BLAZE BY THE "BT" SCRIBING.

MAGNETIC DECLINATION 19 1/2° EAST

WORKED PERFORMED BY: DAVID A. SCHLAICH (RLS 2308)
WITNESSED BY: MYRNA R. NEIL
DATE: OCTOBER 12, 1995

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWS 06/30/96

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 21 day of MAY, 1995
Robert D. Barrett by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SEE MAP OF SURVEY NO. 1389

R-13