CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner set from 1884 survey by Herman D. Gradon under contract with the General Land Office

Set a post from which a:

12" Tamarack bears N 21° E 36 lks

12" Fir bears S 70° E 34 lks

16" Fir bears S 48° W 50 lks

14" Tamarack bears N 64° W 50 lks

DIAGRAM

T9S

S22	S23
S27	S26

R35E

1968

695

Description of corner evidence found:

2½" alum. cap in 1" G.I. pipe 10" out of ground, marked as per diagram above. Set by Hambletton

Fd. Orig. BTs: 24" Larch bears N 21° E 25.0 ft.
22" Fir bears S 70° E 22.6 ft.
25" Larch bears N 64° W 33.8 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

Scribed BTs: 9" W. Fir bears S 12° E 50.7 ft., scribed T9S, R35E S26 BT
17" E. Spruce bears S 20° W 37.6 ft., scribed T9S, R35E S27 BT

I hereby certify the above corner accessory was established as herein described on October 28, 1982

Witnesses: David Dean
Richard Carter

REGISTERED PROFESSIONAL LAND SURVEYOR

James W. Prochnau

OREGON
SEPTEMBER 23, 1977
JAMES W. PROCHNAU
1305

Office of Surveyor *County of* Grant

State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 25 *day of* Jan, 19 83

Robert D. Baggett *by* .....

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

R-17