

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner set from 1884 survey by Herman D. Gradon under contract with the General Land Office

Set a basalt stone 14" x 8" x 6" marked 1/4 on West face from which a:

20" Pine bears N 29° E 42 lks

30" Pine bears S 33° W 39 lks



Description of corner evidence found:

Found original stone 14" x 8" x 6" marked 1/4 on West face

Fd. orig. BT: 35" P. Pine bears S 33° W 39 lks

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2 1/2" brass cap in a 2 1/2" x 30" G.I. pipe with a flared base and rock mound, Corner is marked as per diagram above.

Scribed BTs: 11" D. Fir bears S 55° W 52.2 ft., scribed 1/4 S35 BT
16" P. Pine bears N 35° E 11.2 ft., scribed 1/4 S36 BT

I hereby certify the above corner monument was re-established as herein described on August 3, 1982

Witnesses: David Dean
Richard Carter

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James W. Prochnau
OREGON
SEPTEMBER 23, 1977
JAMES W. PROCHNAU
1305

Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *25* day of *Jan*, 19*83*
Robert D. [Signature] by _____
(COUNTY OFFICIAL) (DEPUTY)