


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File NO-A-17

History of original corner establishment:

Corner was originally established by Herman D. Gradon under G.L.O. contract No. 416, on September 30, 1881. Surveyors General's notes state: "Set a basalt stone 16x10x6 ins. 11 ins. in the ground for cor. to sec.'s 2, 3, 34 & 35 marked with 2 notches on E. and 4 notches on W. edges; from which a pine 24 ins. diam. bears N50°E., 37 lks. dist. marked T9SR35ES35 BT. A fir 18 ins. diam. bears S40°E., 94 lks. dist. marked T10SR35ES2 BT. A fir 12 ins. diam. bears S30°W. 41 lks dist. marked T9SR35ES34 BT.




Description of corner evidence found:

Found aluminum cap on 1 1/4" galvanized pipe stamped; Pipe was tilted and very loose. All original BTs are dead.



Description of monument and accessories I established to perpetuate the original location of this corner:

Firmed up pipe and built mound of stone around to cap. Added number 4 to read S34. From corner monument: A 9" Fir bears N60°E., 39.1 ft. scribed T9SR35ES35 BT. A 12" Fir bears S27°E., 18.6 ft. scribed T10SR35ES2 BT. A 10" Fir bears S50°W., 32.8 ft. scribed T10SR35ES3 BT. A 8" Fir bears N40°W., 41.2 ft. scribed T9SR35ES34 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs. Old BTs have been signed. Placed 54-4 on steel fence post 5' east of the corner.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland

July 2, 1981



Barry B. Barbour
OREGON
 OCT. 17, 1975
BARRY B. BARBOUR
 1051

Office of.....County.....Surveyor..... County of.....Grant.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 20 day of July....., 1981
Robert D. Begett by
 (COUNTY OFFICIAL) (DEPUTY)