



TISS R31E R32E
1/4
S12 S7
1988
RLS 848

(K-2) Pine 6" dia., Bears N15°E, 13.4ft., scribed: 1/4 S7 BT
Fir 6" dia., Bears N21°W, 21 ft., " 1/4 S12 BT

TISS R31E
SW 1/6
S12
1988
RLS 848

(K-2) Pine 12" dia., Bears N15°E, 17.3ft., scribed: SW 1/6 S12 BT
Pine 12" dia., Bears S54°W, 2.7ft., " SW 1/6 S12 BT

TISS R31E
S1/6
S12
1988
RLS 848

(K-2) Pine 12" dia., Bears N 24°W, 19.4ft., scribed: S1/6 S11 BT
Pine 14" dia., Bears N75°E, 21.1ft., " S1/6 S12 BT

TISS R31E
N1/6
S13
1988
RLS 848

(K-2) Set 5/8" iron pin with plastic cap stamped PLS 848 SURVEY MARKER,
and guard post with Bearing Tree & Warning Signs as follows:
South 10.0ft. and East 10.0ft. from the corner.

TISS R31E
NW 1/6
S13
1988
RLS 848

(K-2) Pine 14" dia., Bears N70°E, 5.5 ft., scribed: NW 1/6 S13 BT
Pine 12" dia., Bears S 9°E, 15.4ft., " NW 1/6 S13 BT

TISS R31E
E1/6
S16
1988
RLS 848

(K-2) Fir 8" dia., Bears S16°W, 31.0ft., scribed: CE 1/6 S13 BT
Pine 20" dia., Bears S63°E, 59.0ft., " CE 1/6 S13 BT

TISS R31E
C1/4
S13
1988
RLS 848

(K-2) Pine 14" dia., Bears S67°E, 14.4 ft., scribed: C1/4 S13 BT
Pine 12" dia., Bears S86°W, 61.4ft., " C1/4 S13 BT

TISS R31E
W1/6
S16
1988
RLS 848

(K-2) Pine 12" dia., Bears S11°W, 3.1ft., scribed: CW 1/6 S13 BT
Pine 14" dia., Bears N17°E, 8.8ft., " CW 1/6 S13 BT

TISS R31E
S1/6
S14
1988
RLS 848

(K-2) Pine 18" dia., Bears S59°23'E, 123.4ft., scribed: S1/6 S13 BT
Pine 18" dia., Bears S89°23'W, 269.3ft., " S1/6 S4 BT

TISS R31E
SW 1/6
S13
1988
RLS 848

(K-2) Fir 12" dia., Bears S84°E, 30.3ft., scribed: SW 1/6 S13 BT
Fir 14" dia., Bears S18°W, 22.6ft., " SW 1/6 S13 BT

T15S R31E
SE 1/6
(A-8) 1988
RLS #48

Pine 12° dia., Bears N30°W, 27.0ft., scribed: SE 1/6 S13 BT

Pine 14° dia., Bears S18°E, 15.3ft., " SE 1/6 S13 BT

T15S R31E
EA/S
W/4 S13
(A-2) 1988
S24
RLS #48

A Pine 10" dia., Bears N60°E, 100.5ft., scribed: E 1/6 S13 BT
Set 5'x8"x30" iron pin with plastic cap stamped: PLS #48
SURVEY MARKER, and guard post with Bearing Tree & Warning
Signs, South 3.6ft.

T15S R31E
W/4 S13
(A-2) 1988
S24
RLS #48

Ir 12° dia., Bears N14°W, 9.0ft., scribed: W 1/6 S13 BT
Pine 10° dia., Bears S34°E, 43.6ft., " W 1/6 S24 BT

T15S R31E
NE 1/6
(A-2) 1988
S24
RLS #48

Ir 14° dia., Bears N17°W, 31.9ft., scribed: NE 1/6 S24 BT
Set 14° dia., Bears S88°W, 13.5ft., " NE 1/6 S24 BT

T15S R31E
S1/4
(A-2) 1988
S24
RLS #48

Set 1/2"x30" iron pins with plastic caps marked SURVEY MARKER
PLS #48, and guard posts with Bearing Tree & Warning Signs
North 10.0ft. & West 10.0ft. from the corner.

T15S R31E
S1/4
(A-2) 1988
S24
RLS #48

Set 5/8"x30" iron pins with plastic caps marked SURVEY MARKER
PLS #48, and guard post with Bearing Tree & Warning Signs East
10.0ft. & West 10.0ft. from the corner.

T15S R31E
S24
(A-2) 1988
S24
RLS #48

Ir 20° dia., Bears S37°W, 28.7ft., scribed: U/4 S25 BT
Ir 12° dia., Bears N77°E, 39.4ft., " I/4 S24 BT

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

[Signature]

**OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848**

RECEIVED AND
FILED

MAR 28 1969

OFFICE OF COUNTY SURVEYOR
Robert D. Hayes
Attest: 11/1/12