



BASIS OF BEARINGS

SOLAR OBSERVATION

LEGEND

- Found 1½" galv. iron pipe with attached Grant County Surveyor Brass Cap.
- Found 2½" brass cap set in concrete, 12" below ground, in a 8" cast iron monument case.
- Found monument as shown.
- Found 5%" iron pin of record
- Set ¾"x30" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.
- ☐ Found monument from recorded survey No. ☐ Survey No. appears in box.
- () GLO record bearing and distance.

REFERENCES

Deed Records Book 129 Page 231-240

129 133 136 136 138 254 790-793 496 666 282

Record Map of Survey No.'s 610, 671, 676, 962, 1042, 1065

Circuit Court Case No. 8355

received and filed

Bearings and Distances Between Pins Along the Center of Trowbridge Ditch

SO1*41'31"W 62.65

S32°58'50"E 38.29

S48°19'42"E 80.00

S56°40′17″E 36.44

S63°47'20"E 61.71

S42°39'37"E 69.83

S47°09'35"E 120.66

S51°44'20"E 113.56

931°00'22"E 63.63

S63°32'43"E 87.90

S87°45'49"E 69.75

S72°30'00"E 41.16

S61°18'50"E 147.76

S80°40'44"E 106.46

N86°23'23"E 39.26

*\$85*55′06″E*

S67°23′16″E

S87°11'45"E

APR 2 5 1989



BAGETT - GRIFFITH & ASSOCIATES John Day, Oregon MAP OF SURVEY
OF A TRACT OF LAND SITUATED IN
SECTION 22, TI3S, R3IE, W.M. GRANT COUNTY, OREGON SURVEYED FOR LEO YOUNG R.D.B. & J.L.W. & K.J.W. SURVEYED BY 4/10-12/89

Scale: /" = 300' Drawn by: J.L.W.

4/21/89