



BASIS OF BEARINGS
SOLAR OBSERVATION

LEGEND

- Found 5/8" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.
- Set 5/8"x 30" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.
- x-x Fence line.
- () Record bearing and distance as shown on Record Map of Survey No. 1081.
- Found monument from Recorded Survey No. □ Survey No. appears in the box.

REFERENCES

Record Map of Survey No.'s 704, 782, 1081

NOTE: The section line shown is protracted for general information only.

NARRATIVE: This survey was performed at the request of Carl Sheedy. The purpose of this survey was to delineate the small area shown hereon for boundary adjustment purposes. Also, to relocate a portion of the access easement shown on Map of Survey No. 1081, as shown hereon. The two monuments set on the north line of this survey are set on line and between found monuments set in Survey No. 782. The location of the monuments set during this survey were approved by Mr. Sheedy. I found no unusual conditions with this survey.

RECEIVED AND
FILED

OCT 4, 1990
OFFICE OF COUNTY SURVEYOR

Robert D. Baggett
ATTEST: Carol Baggett, Co. Clerk

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 12, 1983
ROBERT D. BAGGETT
598

BAGETT - GRIFFITH & ASSOCIATES John Day, Oregon		
MAP OF SURVEY BOUNDARY ADJUSTMENT LINE SITUATED IN THE SW 1/4 SE 1/4 OF SEC. 31, T13S, R32E, AND GOV'T LOT 4 OF SEC. 5, T14S, R32E, WM		
GRANT COUNTY, OREGON		
SURVEYED FOR	CARL SHEEDY	
SURVEYED BY	R.D.B. & J.L.W. & G.J.R.	9/5/90
Scale: 1"=50'	Drawn by: J.L.W.	