

NARRATIVE: This survey was performed at the request of Monte Thissell, Dana Jennings and David Kirk, The purpose of this survey was to locate the north 500 feet of the SE1/4SE1/4 of Section 26, and to mark the boundary lines with lath and flagging, as shown hereon.

A search was made of the available records pertaining to this survey. Field measurements were made to locate existing controlling monuments, ie, the four corners of the SE1/4SE1/4 of Section 26, and other monuments as shown, as previously established in Surveys 262, 373, 433 and 519. New monuments were set as shown hereon.

l use the bearing of the line between found monuments at the SE corner of Sec. 26 and the East 1/4 of Sec. 26 as shown on Map of Survey No. 519 for my basis of bearings.

I found no unusual conditions with this survey.



BASIS OF BEARINGS

Record Map of Survey No. 519

LEGEND

- Found 1-1/2" galvanized iron pipe with attached Grant County Surveyor Brass Cap monument.
- Found 5/8" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.
- Set 5/8"x 30" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.
- —x Fence line
- Found monument from Recorded Survey No. Survey No. appears in the box.
- () Record bearing and distance from Survey No. 519

REFERENCES

DEED RECORD INSTRUMENT NO. 911425

RECORD MAP OF SURVEY NO. 262,373,433,467,519

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1983
ROBERT D. BAGETT
598

Expiration Date 12/31/94

RECEIVED AND FILED

Suly 6, 1993
OFFICE OF COUNTY SURVEYOR

Robert D. Sayet

BAGETT - GRIFFITH & ASSOCIATES

John Day Oregon

MAP OF SURVEY A TRACT OF LAND SITUATED IN THE SE1/4SE1/4 OF SECTION 26, T14S, R31E, W.M.

GRANT COUNTY, OREGON

SURVEYED FOR D.JENNINGS, D.KIRK, M.THISSELL
SURVEYED BY RDB & SDF & GJR 6/9/93
Scale: 1"=200' Drawn by: J.L.W.

RECORD MAP OF SURVEY NO.1269