

BASIS OF BEARINGS

SOLAR OBSERVATION

Taken at the SW Corner of Microwave Site

Found 2-1/2" iron pipe with attached 3" brass cap, see corner restoration records.

Set 5/8"x30" iron pin with attached yellow plastic cap marked BGA SURVEY MARKER.

This survey was performed at the request of Don Malmstrom of Affiliated Land Services, Inc., acting in behalf of PTI Communications. The purpose of this survey was to set four corners of a microwave tower site and tie the southwest corner of that tract to the NW corner of Section 6, as shown

A search was made of the available records pertaining to this survey. Field measurements were made to locate the existing monument at the NW corner of section 6. The NW corner of section 6 was remonumented from original evidence in Nov. 1972 by D.M. Ferguson, PLS No. 848. We set new monuments at corners of the microwave site as instructed by Don Malmstrom and PTI Communications, as shown hereon.

During this survey, we ran a closed loop traverse to tie the section corner and to set new monuments at the site.

I found no unusual conditions with this survey.

RECEIVED AND FILED

NOU.19,1993
OFFICE OF COUNTY SURVEYOR

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON JULY 12, 1963
ROBERT D. BAGETT 598

Renewal Date 12/31/94



John Day ,Oregon

10/26/93

MAP OF SURVEY
PTI COMMUNICATIONS MICROWAVE SITE
SITUATED IN THE SE1/4NE1/4 SECTION 6
T8S, R31E, W.M.

GRANT COUNTY, OREGON

SURVEYED FOR PTI COMMUNICATIONS SURVEYED BY RDB & SDF & GJR & DEM

Scale: 1"=20' Drawn by: J.L.W.