

N 1/2 SEC. 34, T 11S, R 35 E, W .M.

NOTES

- ① PT. N14, SET 16mm x 762mm IRON ROD
W/ ODOT ALUM. CAP MARKED "NET 14"
N 103140.073
E 2661291.025
- ② PT. T10, FND. 16mm (5/8") IRON ROD
W/ODOT ALUM. CAP MARKED "TRAV 10"
CS 1206
N 1032129.837
E 2661285.230

FND. 64mm (2 1/2") ALUM. CAP
IN COLLAR OF STONE MARKED
"1/4 S27, S34, LS 1020, 1989", CS 1116
N 103222.886
E 2660900.322

R = 220 m C.L.
TΔ = 45°41'46"
Ts = 122.965 m
2 - 60 m SPIRALS
S = 7°48'47"

R = 290 m C.L.
TΔ = 18°59'04"
Ts = 86.103 m
2 - 75 m SPIRALS
S = 7°24'32"

R = 1200 m C.L.
TΔ = 6°10'40"
Ts = 124.779 m
2 - 120 m SPIRALS
S = 2°51'53"

N11
SET 16mm X 762mm
IRON ROD W/ODOT
ALUM. CAP
MARKED "NET 11"
N 103206.150
E 2661005.070

N12
SET 16mm X 762mm
IRON ROD W/ODOT
ALUM. CAP
MARKED "NET 12"
N 103219.607
E 2661046.136

R = 250 m C.R.
TΔ = 42°37'38"
Ts = 127.759 m
2 - 60 m SPIRALS
S = 6°52'32"

T7
FND 16mm (5/8")
IRON ROD W/ODOT
ALUM. CAP
MARKED "TRAV 7"
CS 1206
N 103066.819
E 2660666.605

N10
SET 16mm X 762mm
IRON ROD W/ODOT
ALUM. CAP
MARKED "NET 10"
N 103100.618
E 2660823.611

N13
SET 16mm X 762mm
IRON ROD W/ODOT
ALUM. CAP
MARKED "NET 13"
N 103140.135
E 2661255.811

N14
SET 16mm X 762mm
IRON ROD W/ODOT
ALUM. CAP
MARKED "NET 14"
N 103133.194
E 2661255.617

SECTION 27
SECTION 34

MALHEUR NATIONAL FOREST

MALHEUR NATIONAL FOREST

- ▲ SET NETWORK POINT
- ☆ FOUND GPS POINT
- △ FOUND MONUMENT USED AS NETWORK POINT
- FOUND 5/8" IRON ROD, OR AS NOTED
- SECTION LINE
- 1/4 SECTION LINE
- 1/16 SECTION LINE
- U.S.F.S. EASEMENT CENTERLINE
- U.S.F.S. EASEMENT LINE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Robert E. Butler
JULY 25, 1995
ROBERT E. BUTLER
2733
EXPIRES 12/31/2003

SCALE 1:2000
1mm = 2.000m
METERS
TO CONVERT METERS TO S. I. FEET DIVIDE BY 0.3048

OREGON DEPARTMENT OF TRANSPORTATION
HORIZONTAL CONTROL, RECOVERY AND RETRACEMENT MAP
OF THE 1953 AND 2000 ALIGNMENT OF THE
JOHN DAY HIGHWAY (AUSTIN JCT. - BAKER CO. LINE SECTION)
GRANT COUNTY, OREGON
AUG. 3, 1999 TO OCT. 17, 2001 FOR O.D.O.T. REGION 5
3012 ISLAND AVE., LA GRANDE, OREGON 97850
2000 ALIGNMENT SHEET 6 OF 21

THIS PLAT USES OACES APPROVED
INK/MYLAR COMBINATION
HP c4871a/51642b