T14S R32E | R33E 1(S89°57'18"W 2652.62) S89°59'37"W 2653.04 C1/4 cor. 1/4 cor. 1580 384 1326.52 1**326.52** 2(1326.32) 1580 2(1326.32) 40.30 Acres 2654.67 NOO'01'29"E 2644.23 (North 2640) 1(NOO'00'19"W 2643.79) 3(NOO'01'29"E 2644.23) BASIS OF BEARINGS 1(NO0'13'33"W 2664.91) NO0'12'16"W 2665.12 S89'46'04"W 2647.74 1323.87 1323.87 12 1321.23 1321.23 1/4 cor. S89'32'27"W 2642.46 384 1(S89°29'51"W 2642.46) 13 18 (N89°46'W 2636.70) Found 5/8" alum. rod with a 3½" alum. cap. Set in 1990 by Elmo Calkins, LS 1805.



Scale 1"=300'

BASIS OF BEARINGS

Survey No. 1672

LEGEND


- Found 1½" iron pipe with attached 2½" Grant County Surveyor brass cap, unless otherwise shown.
- Found 5/8" iron pin with attached yellow plastic cap.
- O Set 5/8"x30" iron pin with attached 2½" alum. cap marked CORNERSTONE SURVEYING, INC. See corner restoration records for details.
- () GLO record bearing and distance.
- 1() Survey No. 384 record bearing and distance.
- 2() Survey No. 1580 record bearing and distance.
- 3() Survey No. 1672 record bearing and distance.
- Found monument, see record map of survey number shown in box.


NARRATIVE

This survey was performed at the request of Richard Friese. The purpose of this survey was to locate and establish the corners of the NE1/4SE1/4 of Section 12, T14S, R32E, W.M.

Section 12 was subdivided in 1975, see Survey No. 384. The C1/4 corner and the NW corner of the NE1/4SE1/4 were established in Survey 1580. I accepted the monuments found during this survey and subdivided the SE1/4 in the usual manner.

received and File D





CORNERSTONE SURVEYING, Inc.

233 S. Canyon Blvd., John Day, Oregon 97845 (541) 575—1813

MAP OF SURVEY
SITUATED IN THE SE1/4 OF SECTION 12
T14S, R32E, W.M.

GRANT COUNTY, OREGON

SURVEYED FOR: RICHARD FRIESE

SURVEYED BY: Jack Watson Date: Aug. 25, 2003