

607

VOL. 689

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTIONS 7 AND 8,
TOWNSHIP 18 SOUTH, RANGE 28 EAST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Nathan C. Erickson, Cadastral Surveyor

Under Special Instructions dated June 2, 2010, approved June 3, 2010,
which provided for the surveys included under Group No. 2334,
and Assignment Instructions dated June 3, 2010.

Survey commenced June 15, 2010

Survey completed June 30, 2010

INDEX DIAGRAM

TOWNSHIP 18 SOUTH RANGE 28 EAST

6	5	4	3	2	1
8	7				
7	8 2	9	10	11	12
5	6 3				
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

T. 18 S., R. 28 E., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 7 and 8, Township 18 South, Range 28 East, Willamette Meridian, Oregon.

The history of official Federal surveys pertaining to this resurvey is as follows:

In 1874, Alonzo Gesner, U.S. Deputy Surveyor, surveyed the east boundary of Township 18 South, Range 27 East.

In 1884, Henry W. Cooke, U.S. Deputy Surveyor, surveyed the subdivisional lines of Township 18 South, Range 28 East.

In 1992-93, Daniel E. Weller, Cadastral Surveyor, dependently resurveyed a portion of the east boundary of Township 18 South, Range 27 East.

The following local surveys filed in the Grant County Courthouse are referred to in subsequent corner description and are referenced by surveyor's last name, Professional Land Surveyor (PLS) No., and year.

<u>Date</u>	<u>Name and Registration Number</u>	<u>File Number</u>
1990	Duane Griffith, PLS No. 644	MOS 1149
1996	Jack L. Watson, PLS No. 2734	MOS 1430
1996	Carl J. Stout, PLS No. 2632	MOS 1430

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions (2009), and the special instructions approved June 3, 2010, for Group No. 2334, Oregon.

The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) techniques and carried forward by sustained angulation using conventional survey techniques. All measurements along the lines were derived through GPS and conventional survey techniques. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted mean bearings and mean horizontal ground elevation distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey the lines of the official original survey(s) and resurvey(s) were retraced and search was made for all corners, lines, other calls of the record, and, where available, collateral evidence of local surveys and corners. Identified corners were perpetuated in their original positions; lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

T. 18 S., R. 28 E., Willamette Meridian, Oregon

FEET	<p>The geographic position (NAD 1983 (2007)) of the following corner as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online User Positioning Service (OPUS):</p> <p>The corner of sections 8, 9, 16, and 17.</p> <p>Latitude: 44° 01' 00.11" N. Longitude: 119° 22' 33.54" W.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 18 S., R. 28 E., Willamette Meridian, Oregon</p> <hr/> <p align="center">Restoring the survey by Henry W. Cooke in 1884</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17, monumented with the original basalt stone, 14 x 13 x 13 ins., (Record, 16 x 12 x 10 ins.) firmly set, projecting 5 ins. above the ground, mkd. with 4 notches on S. and E. edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T 18 S</td><td>R 28 E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td colspan="2">2010</td></tr> </table> </div> <p>Raised mound of stone, 3 ft. at base, 1 1/2 ft. high, 3 ft. S of cor.</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, erroneously established by Jack L. Watson, PLS No. 2734; in 1996, as the cor. of secs. 8, 9, 16, and 17, bears N. 22° 05' 08" E., 156.70 ft. dist., with aluminum cap mkd. T 18 S R 28 E S8 S9 S17 S16 1996 OPLS 2734</p> <p>The 5/8 in. diam. iron rods set by Watson as accessories were not tied.</p> <p>N. 0° 02' 47" E., bet. secs. 8 and 9.</p> <p>405 John Day Creek.</p> <p>2310 Top of ridge.</p> <p>2640.08 Point for the 1/4 cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p>	T 18 S	R 28 E	S 8	S 9	<hr/>		S 17	S 16	2010	
T 18 S	R 28 E										
S 8	S 9										
<hr/>											
S 17	S 16										
2010											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 18 S R 28 E 1/4 S 8 S 9 2010</p> <p>from which</p> <p>A juniper, 11 ins. diam., bears S. 69° W., 99.5 ft. dist., mkd. 1/4 S8 BT.</p> <p>A juniper, 21 ins. diam., bears N. 3° W., 244.1 ft. dist., mkd. X BT.</p> <p>5280.16 The cor. of secs. 4, 5, 8, and 9, determined at the center of the original mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p align="center">T 18 S R 28 E S 5 S 4 S 8 S 9 2010</p> <p>from which</p> <p>A juniper, 20 ins. diam., bears N. 48° E., 185.8 ft. dist., mkd. T18S R28E S4 BT.</p> <p>A twin juniper, 23 ins. diam., bears S. 72 1/4° E., 165.1 ft. dist., mkd. T18S R28E S9 BT on the northerly trunk.</p> <p>A juniper, 16 ins. diam., bears N. 56 1/4° W., 58.3 ft. dist., mkd. T18S R28E S5 BT.</p> <p>No other accessories available.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>S. 88° 52' 50" W., bet. secs. 8 and 17.</p> <p>2647.58 The 1/4 cor. of secs. 8 and 17, monumented with the original basalt stone, 16x 14 x 10 ins., firmly set, projecting 8 ins. above the ground, with collar of 3 stones, mkd. with illegible chisel marks.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 18 S R 28 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2010</p> </div> <p>Raised mound of stone, 3 ft. base, 20 ins. high, 5 ft. S. of cor.</p> <p>Bury original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 56' 59" W., bet. secs. 8 and 17, beginning new measurement.</p> <p>1287.70 Point for the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 8</p> <p>W 1/16 ———</p> <p>S 17</p> <p>2010</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 63 3/4° E., 60.9 ft. dist., mkd. W 1/16 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 54 1/4° E., 28.5 ft. dist., mkd. W 1/16 S17 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>2575.40 The cor. of secs. 7, 8, 17, and 18, monumented with the original basalt stone, 23 x 11 x 11 ins., (Record, 24 x 14 x 10 ins.) firmly set, projecting 16 ins. above the ground, in a mound of stone, 2 1/2 ft. base, 12 ins. high, mkd. with 4 grooves on S. edge and 5 grooves on the E. edge, from which the remains of original bearing trees:</p> <p style="padding-left: 40px;">A pine log with scribe marks T18S R28E S8 BT visible, no evidence of stump.</p> <p style="padding-left: 40px;">A pine, badly degraded, bears N. 27 3/4° W., 73.2 ft. dist., with scribe marks BT visible. (Record; N 32° W, 72.6 ft.)</p> <p>At the corner point</p>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T 18 S</td><td>R 28 E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td colspan="2">2010</td></tr> </table> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears N. 46 3/4° E., 23.6 ft. dist., mkd. T18S R28E S8 BT.</p> <p>A fir, 10 ins. diam., bears S. 27 1/4° E., 64.3 ft. dist., mkd. T18S R28E S17 BT.</p> <p>A fir, 14 ins. diam., bears S. 19° W., 9.9 ft. dist., mkd. T18S R28E S18 BT.</p> <p>A fir, 10 ins. diam., bears N. 13 3/4° W., 24.9 ft. dist., mkd. T18S R28E S7 BT.</p> <p>Bury the original stone alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor., an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, 2 1/2 ft. diam., erroneously established by Jack L. Watson, PLS No. 2734, in 1996; as the cor. of secs. 7, 8, 17, and 18, bears N. 11° 03' 38" W., 100.85 ft. dist., monumented with an aluminum cap mkd. T 18 S R 28 E S7 S8 S18 S17 1996 OPLS 2734</p> <hr/> <p>S. 88° 11' 15" W., bet. secs. 7 and 18, beginning new measurement.</p> <p>2535 Barb wire fence, extending N. 85° E. and S. 85° W.</p> <p>2664.74 The 1/4 cor. of secs. 7 and 18, perpetuated by Jack L. Watson, PLS No. 2734, in 1996, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with an aluminum cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T 18 S</td><td>R 28 E</td></tr> <tr><td>S 7</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 18</td><td></td></tr> <tr><td>1996</td><td></td></tr> <tr><td>OPLS 2734</td><td></td></tr> </table> </div> <p>from which bearing trees by Jack L. Watson, PLS No. 2734</p>	T 18 S	R 28 E	S 7	S 8	<hr/>		S 18	S 17	2010		T 18 S	R 28 E	S 7		<hr/>		1/4		S 18		1996		OPLS 2734	
T 18 S	R 28 E																								
S 7	S 8																								
<hr/>																									
S 18	S 17																								
2010																									
T 18 S	R 28 E																								
S 7																									
<hr/>																									
1/4																									
S 18																									
1996																									
OPLS 2734																									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	
	<p>A sawed pine stump, 14 ins. diam., bears N. 50° E., 16.3 ft. dist., with washer mkd. PLS 2734 nailed to face.</p> <p>A juniper, 7 ins. diam., bears S. 79 1/2° E., 20.2 ft. dist., mkd. 1/4 S18 on high blaze and BT at base blaze.</p> <p>A sawed pine stump, 14 ins. diam., bears S. 40° W., 18.2 ft. dist., with washer mkd. PLS 2734 nailed to face.</p> <p>A sawed fir stump, 14 ins. diam., bears N. 20° W., 11.3 ft. dist., cut low to ground, no mks. visible.</p> <p>and new bearing tree</p> <p>A ponderosa pine, 8 ins. diam., bears N. 27 1/4° W., 18.7 ft. dist., mkd. 1/4 S7 BT.</p> <p>Found original basalt stone, 14 x 12 x 10 ins., on N. side of collar of stone, mkd. 1/4 on face. No remaining evidence of the original bearing trees.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 10' 45" E., bet. secs. 7 and 8.</p>
635	Dirt road, 20 ft. wide, extending N. 70° E. and S. 70° W.
905	Creek, 20 ft. wide, course N. 55° E.
1020	Barb wire fence, extending E and W.
1325.86	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16</p> <p>S 7 S 8</p> <p>2010</p> </div>
	<p>Raised mound of stone, 2 1/2 ft. base, 15 ins. high, 3 ft. N. of cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
2651.72	<p>Point for the 1/4 cor. of secs. 7 and 8, set at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	<div data-bbox="803 430 982 546"> <p align="center">T 18 S R 28 E 1/4 S 7 S 8 2010</p> </div> <p>from which</p> <p>A juniper, 17 ins. diam., bears S. 54 1/2° W., 12.5 ft. dist., mkd. 1/4 S7 BT.</p> <p>A juniper, 24 ins. diam., bears N. 1 1/2° W., 28.2 ft. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>5303.44 The cor. of secs. 5, 6, 7, and 8, remonumented by Carl J. Stout, PLS No. 2632, in 1996, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with an aluminum cap mkd.</p> <div data-bbox="803 997 982 1165"> <p align="center">T 18 S R 28 E S 6 S 5 —+— S 7 S 8 1996 LS 2632</p> </div> <p>from which bearing trees by Stout</p> <p>A juniper, 19 ins. diam., bears N. 27 1/4° E., 133.1 ft. dist., with scribe marks T18S R28E S5 visible on partially healed high blaze and BT at base blaze, washer in face, mkd. PLS 2632.</p> <p>A juniper, 16 ins. diam., bears S. 52 3/4° E., 187.3 ft. dist., with scribe marks T18S R28E S8 BT visible on partially healed blaze, washer in face, mkd. PLS 2632.</p> <p>A juniper, 19 ins. diam., bears S. 56 1/2° W., 97.5 ft. dist., with scribe marks T18S R28E S7 BT visible on open blaze, washer in face, mkd. PLS 2632.</p> <p>A juniper, 18 ins. diam., bears N. 26 1/2° W., 80.7 ft. dist., with scribe marks T18S R28E S6 visible on open high blaze and BT at base blaze, washer in face, mkd. PLS 2632.</p> <p>Found original basalt stone, 18 x 14 x 10 ins. (Record, 16 x 14 x 12 ins.), on S. side of collar of stone, mkd. with 5 notches on S. and E. edges.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	
2587.68	<p>S. 89° 20' 24" W., bet. secs. 5 and 8.</p> <p>The 1/4 cor. of secs. 5 and 8, remonumented by Jack L. Watson, PLS No. 2734, in 1996, and recorded in the Grant County Surveyor's Office Corner Monumentation records, monumented with an aluminum post, 2 1/2 ins. diam., loosely set, projecting 16 ins. above the ground, in a mound of stone, 2 1/2 ft. base, 12 ins. high, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 18 N R 28 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>1996</p> <p>LS 2734</p> </div> <p>from which bearing trees by Watson</p> <p>A juniper, 16 ins. diam., bears N. 63 3/4° E., 88.9 ft. dist., with scribe marks 1/4 S5 BT visible on partially healed blazes.</p> <p>A juniper, 19 ins. diam., bears S. 33 1/2° E., 55.9 ft. dist., with scribe marks 1/4 S8 BT visible on partially healed blazes.</p> <p>A juniper, 18 ins. diam., bears N. 80 3/4° W., 96.0 ft. dist., with incorrect scribe marks 1/4 S8 BT visible on partially healed blazes.</p> <p>A juniper, 18 ins. diam., bears N. 61° W., 90.1 ft. dist., with scribe marks 1/4 S5 and BT visible on partially healed blazes.</p> <p>Found original basalt stone, 14 x 9 x 7 ins. (Record, 16 x 14 x 12 ins.), on N. side of mound of stone, mkd. with 1/4 on the N. face.</p> <p>Firm up monument and rebuild mound of stone to top of cap.</p> <hr/> <p>S. 88° 59' 52" W., bet. secs. 5 and 8, beginning new measurement.</p>
2621.38	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr/> <p>S. 88° 11' 18" W., bet. secs. 6 and 7.</p>
2668.49	<p>The 1/4 cor. of secs. 6 and 7, monumented with the original basalt stone, 16 x 16 x 5 ins., firmly set, projecting 7 ins. above the ground, mkd. 1/4 on N. face, from which a mound of stone, 1 1/2 ft. diam., 18 ins. high, bears N, 3 ft. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">T 18 N R 28 E S 6 1/4 ——— S 7 2010</p> <p>from which new bearing trees</p> <p>A juniper, 14 ins. diam., bears N. 50 1/4° E., 42.0 ft. dist., mkd. 1/4 S6 BT.</p> <p>A juniper, 12 ins. diam., bears S. 55° E., 19.2 ft. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 18 S., R. 28 E., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 cor. of secs. 7 and 18.</p> <p>N. 0° 07' 54" E., on the N. and S. centerline of sec. 7.</p> <p>690 Centerline of dirt road, 18 ft. wide, extending S. 65° E. and N. 65° W.</p> <p>820 Barb wire fence, extending E and W.</p> <p>1130 Creek, 11 ft. wide, course E.</p> <p>1325.50 Point for the center S 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 7 C 2010</p> <p>from which</p> <p>A ponderosa pine, 21 ins. diam., bears S. 65 1/2° E., 131.9 ft. dist., mkd. C S 1/16 S7 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 29 1/4° W., 69.2 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 7,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	
2651.00	<p>The center 1/4 cor. of sec. 7, set at intersection with the E. and W. centerline of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 18 S R 28 E C 1/4 S 7 2010</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 43 3/4° E., 56.1 ft. dist., mkd. C 1/4 S7 BT.</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S. 28 1/4° W., 100.9 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5303.36	<p>The 1/4 cor. of secs. 6 and 7.</p> <hr/> <p>From the 1/4 cor. of secs. 7 and 8.</p> <p>S. 88° 10' 24" W., on the E. and W. centerline of sec. 7.</p>
2666.63	<p>The center 1/4 cor. of sec. 7.</p>
5299.05	<p>The 1/4 cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, in a scattered mound of stone, with a brass cap mkd.</p> <p style="text-align: center;">T 18 S R 27 E R 28 E 1/4 S 12 S 7 1992</p> <p>from which bearing trees by Weller</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S. 81 1/4° E., 30.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 32 1/2° W., 126.9 ft. dist., with a healed blaze. (Record, 127.9 ft.)</p> <p>Rebuilt mound of stone at cor., 3 ft. base, to top.</p> <hr/>

**Subdivision of Section 7,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	
2665.68	<p>From the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>S. 88° 10' 49" W., on the E. and W. centerline of the SE 1/4 of sec. 7.</p> <p>The center S 1/16 sec. cor. of sec. 7.</p>
1324.09	<p style="text-align: center;">Subdivision of Section 8, T. 18 S., R. 28 E., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 cor. of secs. 8 and 17.</p> <p>N. 0° 40' 59" E., on the N. and S. centerline of sec. 8.</p> <p>Point for the center S 1/16 sec. cor. of sec. 8, not monumented.</p>
2648.18	<p>Point for the center 1/4 cor. of sec. 8, set at the intersection with the E. and W. centerline of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 3 1/2 ft. base, 18 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T 18 S R 28 E C 1/4 S 8 2010</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 41 1/4° E., 20.7 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N. 80 3/4° W., 73.0 ft. dist., mkd. C 1/4 S 8 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5302.44	<p>The 1/4 cor. of secs. 5 and 8.</p>
2617.69	<hr/> <p>From the 1/4 cor. of secs. 8 and 9.</p> <p>S. 89° 02' 28" W., on the E. and W. centerline of sec. 8.</p> <p>The center 1/4 cor. of sec. 8.</p>
3916.84	<p>Point for the center W 1/16 sec. cor. of sec. 8, not monumented.</p>
5215.99	<p>The 1/4 cor. of secs. 7 and 8.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 8 and 17.</p>

**Subdivision of Section 8,
T. 18 S., R. 28 E., Willamette Meridian, Oregon**

FEET	N. 0° 25' 51" E., on the N. and S. centerline of the SW 1/4 of sec. 8.
110	Barb wire fence, extending E. and W.
375	Dirt road, 18 ft. wide, extending S. 65° E. and N. 65° W.
635	Creek, 10 ft. wide, course E.
940	Creek, 4 ft. wide, course N. 80° E.
1060	Barb wire fence, extending E. and W.
1324.96	Point for the SW 1/16 sec. cor. of sec. 8, at its calculated position. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. SW 1/16 S 8 2010 from which A twin juniper, 16 ins. diam., bears N. 59 1/2° E., 122.6 ft. dist., mkd. X BT on southerly trunk. A twin juniper, 18 ins. diam., bears S. 72 1/2° E., 195.9 ft. dist., mkd. SW 1/16 S8 BT on southerly trunk. Deposit a magnet in a white plastic case at the base of the stainless steel post. _____ S. 88° 59' 44" W., beginning new measurement, on the E. and W. centerline of the SW 1/4 of sec. 8.
1293.43	The S 1/16 sec. cor. of secs. 7 and 8. _____

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

I, Nathan C. Erickson, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing the approval date of the 3rd day of June, 2010, and assignment instructions bearing the date of the 3rd day of June, 2010, I have dependently resurveyed a portion of the subdivisional lines, and subdivided sections 7 and 8, Township 18 South, Range 28 East, Willamette Meridian, Oregon, which are represented in the foregoing field notes as having been executed by me and under my direction, and said survey has been made in strict conformity with said special instructions, the Manual of Instructions, and in specific manner described in the foregoing field notes.

6/03/2011

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Portland, Oregon

The foregoing field notes of dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 7 and 8, T. 18 S., R. 28 E., Willamette Meridian, Oregon, executed by Nathan C. Erickson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

June 23, 2011

(Date)



(Chief Cadastral Surveyor of Oregon)