



Scale 1"=200'

BASIS OF BEARINGS

SURVEY NO. 1026

LEGEND

- Found 5/8" iron pin with attached yellow plastic cap, unless otherwise shown.
- Set 5/8"x30" iron pin with attached red plastic cap marked CORNERSTONE SURVEYING, INC.

x——x Fence Line

Survey No. 436 record bearing and distance.

Survey No. 457 record bearing and distance.

Survey No. 1026 record bearing and distance.

Partition No. 2016-08 record bearing and distance.

Deed record bearing and distance.

Found monument, see record map of survey number shown in box.

RECEIVED AND FILED GRANT COUNTY SURVEYOR


FEB 4 2021

NARRATIVE

This survey was performed at the request of Philip Gagnon. The purpose of this survey was to locate and monument the corners of Mr. Gagnon's property as described in Instrument No.s 20210136 and 20210191.

A search was made of the available records pertaining to this survey. Field measurements were made to locate the existing monuments and the new corner positions. I accepted the found corners from Survey No.'s 436 and 1026 as shown hereon. I established the property corners at deed record bearing and distance from the accepted found monuments as shown.

This survey was performed using RTK GPS receivers.



CORNERSTONE SURVEYING, Inc.

233 S. Canyon Blvd., John Day, Oregon 97845 (541) 575-1813

MAP OF SURVEY PROPERTY LINE ADJUSTMENT SITUATED IN SECTION 29 AND SECTION 30 T13S, R32E, W.M.

GRANT COUNTY, OREGON SURVEYED FOR: Philip Gagnon

SURVEYED BY : Jack Watson SURVEY COMPLETED: 02/01/2021