Sheet 7 of 9

520200 - W1/16 COR. OF SECS. 26 & 35, T12S, R30E

T12S R30E W1/16 S35 1983 PLS 848

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor.

Record states:

Corner not previously established Set a 30"x2" aluminum pipe with 31/2" aluminum cap, stamped as shown in diagram. Set 12" in the ground & raised a mound of stone around pipe.

A Juniper 13" dia. bears N81 °E, 42.0 ft. scribed W1/16 S26 BT. A Juniper 9" dia. bears S58 W, 23.4 ft. scribed W1/16 S35 BT.

Subsequent Monumentation:

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 2½ ins. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 3 ft. base to top with aluminum cap mkd. as shown.

From which bearing trees by Ferguson: A juniper, 15 ins. diam., alive and healthy, bears N. 81°E., 42.0 ft. dist., with visible scribe on open blaze. A juniper, 10 ins. diam., alive and healthy, bears S. 58°W., 23.4 ft. dist., with visible scribe on open blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/19/2021

520220 - SW1/16 COR. OF SEC. 26, T12S, R30E

T12S R30E SW1/16 S26 PLS 848

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor.

Record states:

Corner not previously established.

Set a 30"x2" aluminum pipe with a 31/2" aluminum cap, stamped as shown in diagram. Set 24" in the ground.

A Pine 9" dia. bears N1 °E, 7.6 ft. scribed SW1/16 S26 BT. A Pine 9" dia. bears N54°E, 10.6 ft. scribed SW1/16 S26 BT.

Subsequent Monumentation:

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as

From which bearing trees by Ferguson:

A ponderosa pine, 20 ins. diam., alive and healthy, bears N. 54° E., 10.6 ft. dist., with healed blaze. A ponderosa pine, 14 ins. diam., alive and healthy, bears S. 1 ° W. (record N.1 ° E.), 7.6 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/19/2021.

520240 - CW1/16 COR. OF SEC. 26, T12S, R30E

T12S R30E W1/16 C----C S26 1983 PLS 848

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor.

Record states: Corner not previously established.

Set a 30"x2" aluminum pipe with a 31/2" aluminum cap stamped as shown in diagram. Set 24" in ground. From which:

A Pine 5" dia. bears N77 W, 8.8 ft. scribed X BT. A Pine 7" dia. bears S57°E, 64.2 ft. scribed CW1/16 S26 BT.

Subsequent Monumentation:

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 21/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base to top with aluminum cap mkd. as shown.

From which bearing trees by Ferguson:

A ponderosa pine, 15 ins. diam., alive and healthy, bears S. 57° E., 64.2 ft. dist., with healed blaze. A ponderosa pine, 9 ins. diam., alive and healthy, bears N. 77° W., 8.8 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/18/2021.

520260 - NW1/16 COR. OF SEC. 26, T12S, R30E

T12S R30E NW1/16 S26 **PLS 848**

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor. Record states:

Corner not previously established.

Set a 30"x2" aluminum pipe with a 31/2" aluminum cap stamped as shown in diagram. Set 16" in ground & raised mound of stone & earth around pipe.

A Pine 9" dia. bears S60°W, 12.4 ft. scribed NW1/16 S26 BT.

A Pine 7" dia. bears S7°E, 13.9 ft. scribed NW1/16 S26 BT.

Subsequent Monumentation: None

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 21/2 ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 3 ft. base to top with aluminum cap mkd. as shown.

From which bearing trees by Ferguson:


A ponderosa pine stump hole bears S. 7° E., 13.9 ft. dist., with visible scribe on open blaze remains. A ponderosa pine, 20 ins. diam., alive and healthy, bears S. 60°W., 12.4 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

A juniper, 8 ins. diam., bears N. 2° E., 17.8 ft. dist., scribed X BT.

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/18/2021.

540200 - 1/4 COR. OF SECS. 26 & 35, T12S, R30E



HISTORY OF ORIGINAL CORNER ESTABLISHED:

Original corner set by Samuel W. Lackland, under contract number 415, approved March 10, 1882. Record states:

Set Basalt Stone 15x9x9 ins., 12 ins. in ground for 1/4 Sec. Cor. marked with 1/4 on N. face. Raised mound of stone 2 ft. high 4 ft. base alongside.

Subsequent Monumentation:

Corner reestablished by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor. Record states:

Corner is on East slope on rocky ground. E/W fence running through the area. Fencing activity has destroyed all evidence. Set position by proportion.

Set a 30"x2" aluminum pipe with a 31/2" aluminum cap, stamped as shown in diagram. Set 16" in the ground & raised a mound of earth and stone around pipe.

A Pine 8" dia. bears N3°W, 10.6 ft. scribed 1/4 S26 BT

A Juniper 20" dia. bears S65°W, 4.6 ft. scribed 1/4 S35 BT.

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with stone collar and aluminum cap mkd. as shown.


From which bearing trees by Ferguson:

A juniper, 20 ins. diam., alive and healthy, bears S. 65° W., 4.6 ft. dist., with visible scribe on open blaze. A ponderosa pine, 12 ins. diam., alive and healthy, bears N. 3° W., 10.6 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/18/2021.

540240 - C1/4 COR. OF SEC. 26, T12S, R30E



HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor. Record states:

Corner not previously established.

Set a 5/8 iron pin with 1" aluminum cap, stamped PLS848, on South edge of Grouse Creek.

Set a 30"x2" aluminum pipe with 31/2" aluminum cap, stamped as shown in diagram. Set 28" in ground. Bears South on center section line 13.8 ft.

A Fir 10" dia. bears N88 W, 17.0 ft. scribed C1/4 S26 BT.

A Fir 12" dia. bears N53°E, 20.7 ft. scribed C1/4 S26 BT.

Subsequent Monumentation:

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a 5/8 iron pin with 1" aluminum cap, on South edge of Grouse Creek, firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as shown. From which Accessories by Ferguson:


A fir, 14 ins. diam., alive and healthy, bears N. 53° E., 20.7 ft. dist., with healed blaze.

An aluminum cap reference monument bears S. 0° E., 13.8 ft. dist. A fir, 11 ins. diam., alive and healthy, bears N. 88°W., 17.0 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/18/2021.

560220 - SE1/16 COR. OF SEC. 26, T12S, R30E



HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner established by Douglas M. Ferguson, LS 848, as described by Corner Record filed August 29, 1983, in the office of the Grant County Surveyor.

Record states:

Corner not previously established. Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram. Set 25" in ground.

A Fir 11" dia. bears N7°E, 38.9 ft. scribed SE1/16 S26 BT. A Fir 12" dia. bears S66°E, 42.6 ft. scribed SE1/16 S26 BT.

Subsequent Monumentation:

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found an aluminum pipe, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. as

From which bearing trees by Ferguson:
A fir, 18 ins. diam., alive and healthy, bears N. 7° E., 38.9 ft. dist., with healed blaze.
A fir, 20 ins. diam., alive and healthy, bears S. 66° E., 42.6 ft. dist., with healed blaze.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER: (See NOTES on Sheet 1)

Witnesses: Matt Brockamp, LS & Austin Brockamp on 6/18/2021.

REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON MATTHEW R. BROCKAMP

78556 Registration expires 12/31/2021

BROCKAMP LAND SURVEYING, LLG Matt Brockamp, PLS PO. Box f Wallowa, OR 9788

Full Service Land Survey Firm