



BASIS OF BEARINGS

SURVEY NO. 322

1/4 cor. not searched for.

11
14

Sec. cor. not fd.

11 12
14 13

NW 1/4 NE 1/4

67 ac.±

NE 1/4 NE 1/4

91 ac.±

S 0°16'28"W 2720.89 between pins.

Pin:
N 3427.10
W 8020.92

S 89°22'00"W 1722.55 between pins.

SW 1/4 NE 1/4

Pin:
N 3446.14
W 6298.48

SE 1/4 NE 1/4

Pin:
N 3380.46
W 4934.33

Δ = 56°36'
R = 318.31
L = 314.44

Δ = 36°24'
R = 1432.40
L = 918.34

LEGEND

○ Set 5/8"x30" iron pin

NOTE:

1. Sec. lines & 1/16 lines are approximate.
2. Data for county road is record & data, no R.O.W. monuments were found.
3. All coordinates of iron pins refer to the SE cor. Sec. 13, T.8S., R.27E., W.M., which is monumented with Co. Sur. brass cap.

RECEIVED AND
FILED

OCT 2 1974

JOHN LIVEIRA, County Clerk
By *Petty Rowley*, Deputy

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Robert D. Bagett
OREGON
JULY 12, 1963
ROBERT D. BAGETT
598

BAGETT, GRIFFITH & ASSOCIATES

John Day, Oregon

Map of Survey

TRACT SITUATED IN SECS. 11, 12, 13, & 14
T.8S., R.27E., W. M.

GRANT COUNTY, OREGON

SURVEYED FOR	STANLEY MUSGRAVE	
SURVEYED BY	R.D.B. & R.B.C.	9-5-74
Scale: 1" = 200'	Drawn by: R.D.B.	9-10-74