

Fd. 1/4 as set by Michael Spears,  
county surveyor, in June 1909.  
Fd. stone 14"x14"x14" mkd. 1/4

(SPEARS)  
(S 89° 45' E 40.075 chs.)  
2657.78

PIN OFFSET  
27.33

3 2  
10 11

T.14S., R.31E., W.M.

1639.29

S 89° 48' 00" E

938.20

36.0 Ac.

1699.41

NORTH

POWERLINE

OLD IZEE - CANYON CITY COUNTY ROAD

APPROX. SEC. LINE

**BASIS OF BEARINGS**  
SOLAR OBSERVATION

### LEGEND

- FD. B.L.M. BRASS CAP AT SEC. COR.
- SET 5/8"X30" IRON PIN
- ( ) RECORD BEARING & DISTANCE
- x-x FENCE

### REFERENCE:

SURVEYOR RECORD BOOK 1, PAGE 26-28  
SURVEY BY M. SPEARS

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Robert D. Baggett*

OREGON  
JULY 12, 1963  
ROBERT D. BAGGETT  
598

PIN OFFSET  
29.90

A=4° 08' 00"  
L=36.07  
R=500.00

N 84° 42' 18" W

612.15

A=76° 06' 40"  
L=265.68  
R=200.00

A=20° 41' 57"  
L=108.38  
R=300.00

### NOTE:

All road data pertains to centerline.

Acreage calculated to a line within 8' of road centerline.

RECEIVED AND  
FILED

APR 18 1977

JOHN LIVIERA, County Clerk

By \_\_\_\_\_ Deputy

BAGETT, GRIFFITH & ASSOCIATES  
John Day, Oregon

Map of Survey

TRACT LOCATED IN THE NE1/4NE1/4

AND IN THE SE1/4NE1/4 SEC. 10, T.14S., R.31E., W.M.

GRANT COUNTY, OREGON

SURVEYED FOR	EARL BARNARD	
SURVEYED BY	R.D.B. & W.G.	3-77
Scale: 1"= 100'	Drawn by: W. G.	4-77