SUMMARY OF CORNER SEARCH AND EVIDENCE FOUND ROCK OUTCROP. A BASALT STONE 18"X14"X10" [RECORD SIZE] WITH NO *5*17 *5*16 T135R35E ORIGINAL CORNER STONE AND STONE MOUND DESTROYED WHEN LOGGING ROAD WAS PINE BEARS N. 2°W., 15.5 FT. TO FACE W S V. 5. "13 R 35". FOUND ROOT HOLE BUILT THROUGH CORNER LOCATION. LOCATION TAGS ON A 32" PONDEROSA PINE AT POSSIBLE POSITION OF NE BT, BEARS N.42°E., 19 FT. TO CENTER. SNAG NOTES CORNER IS 25 FT. WEST OF TREE. U.S.FS. RECORDS INDICATE B.3 P. 35-36. ORIG. BASALT STONE 24"X 16"X 12" MARKED WITH 4 NOTCHES ON SOUTH AND EAST FOUND BASALT STONE 16"X10"X6" NO VISIBLE MARKINGS FIRMLY SET IN T135 R35E FACES SET 12" IN STONE MOUND WAS FOUND HERE AS LATE AS 1963. COR-MOUND OF STONES ~ 10 OTHER STONES. FOUND ORIG. BT, A 25" PONDEROSA NER CONSIDERED OBLITERATED AND MONUMENTED AS PER TAGS. B.3 P.37-38. PINE, BEARS N. 68°E., 10.6 FT. TO FACE WS V.S. "45". B. 3 P. 25-26. NO ORIGINAL EVIDENCE FOUND AFTER DILIGENT SEARCH AT PROBABLE COR-517 | 516 NER AREAS. CONSIDERED LOST AND RE-ESTABLISH BY SINGLE PROPOR-FOUND ORIG. BASALT STONE ZO"X8"X6" MARKED WITH 2 GROOVES SOUTH FACE 9 519 520 4 516 AND 5 GROOVES EAST FACE LYING OVER IN MOUND OF 6 OTHER STONES. FOUND TION. B. 3 P.47-48. FOUND ORIGINAL BASALT STONE 16"X12"X10" MARKED WITH 4 NOTCHES SOUTH 530 529 REMAINS ORIG. NE BT, A 26" PONDEROSA PINE, DEAD & DOWN, BEARS N.88°E., 54.1 FT. TO ROOT HOLE W.S V.S. " ZOBT". FOUND ORIG. SW BT AN 8" MAHOGANY EDGE SET IN STONE MOUND OF 10 OTHER STONES SUNKEN BELOW DUFF 59 510 516 515 SURFACE, FOUND ORIG. BT, A 19" TAMARACK BEARS 5.80°E., 36.9 FT. TO FACE, DEAD & DOWN, BEARS 5.10°E., 6.0 FT. W.J.V.S. "530BT". B.3 P.27-28. FOUND ORIG. BASALT STONE 11"X 10"X 4" MARKED " 1 " ON WEST FACE FIRMLY WHICH I OPENED TO REVEAL V.S. OF "STIBR3". B. 3 P. 41-42. FOUND ORIG. BASALT STONE 24"X15"X10" MARKED " 4 " ON UPPER FACE LYING SET IN MOUND OF G OTHER STONES. FOUND ORIG. BT, A 36" PONDEROSA DISTURBED AND OUT OF POSITION. FOUND REMAINS OF ORIGINAL STONE MOUND PINE STUMP 14" HIGH WS V.S. "T" BEARS 5.66° E., 20.2 FT. TO FACE. 519 520 IN PLACE ~ SOMEWHAT SCATTERED BY TRACTOR LOGGING. FOUND ORIG. BT, A 17" WHITE FIR BEARS 5.27°W., 21.8 FT. TO FACE, WHICH I OPENED TO RE-FOUND ORIG. BASALT STONE 24"X18"X8" MARKED WITH 3 GROOVES SOUTH FACE T135 R35E 518 | 517 STONES. FOUND ORIG. NW BT, A 27" PONDEROSA PINE BEARS N.5°W., 38.8 FOUND ORIG. BASALT STONE 14"X 8"X 5" MARKED WITH 3 NOTCHES EAST \$ SOUTH T135R35E 516 | 515 EDGES AND "+" ON TOP, SET IN STONE MOUND OF 6 OTHER STONES. FOUND FT. TO FACE WSV.S. "TIRT". FOUND REMAINS OF ORIG. NE BT A ROTTED 521 522 ORIG. NE BT, A 10"LODGEPOLE PINE, DEAD & DOWN, BEARS N. 12°E., G.O FT., PONDEROSA PINE, DEAD & DOWN, BEARS N. 38°E., 38.9 FT., VERY ROTTEN W_SV.5. "5/5T/3R35". FOUND ORIG. SW BT, AN 8" LODGEPOLE PINE, DEAD € NO MARKS VISIBLE. B. 3 P. 31-32. DOWN, BEARS 5.20°W., 7.3 FT. W.J V.S. "521713R35". B. 3 P. 33-34. NO ORIGINAL EVIDENCE FOUND AFTER DILIGENT SEARCH AT PROBABLE CORNER T135R35E AREAS. CONSIDERED LOST AND RE-ESTABLISH BY SINGLE PROPORTION. FOUND STONE MOUND WORKING CORNER SET BY U.S.F.S. PERSONNEL BEARS G.L.O. ~1881~ 589°53'W~40.12 CH5. 5.20°E., 22.7 FT. ~ MOVED STONES TO CAP. B. 3 P. 43-45. G.L.O.~1881~589°53'W~40.12 CH5. 587°10′05″W .587°10′05″W F~2516.25 M~ 766.955 F~2516.25 M~766.955 516 515 516 PRIVATE METERS **SCALE** 588°44'25"W 588°44'25"W 522 F~2528.51 F~2528.51 521 529 M~770.691 M~770.691 G.L.O.~1881~N89°50'W~39.88 CH5. G.L.O.~1881~N89°50'W~39.88 CH5. U. S. F. S.

FOUND LARGE STONE MOUND 3 FT. BASE 2 112 FT. HIGH ON EDGE OF SHARP

CORNER MONUMENTATION AND CORNER ACCESSORIES

T135R35 N 1/16 519 | 520 1981 L51026

FOUND STONE MOUND WORKING CORNER BEARS 5.61°E., 3.2 FT. FROM CORNER. SET MONUMENT 18" IN GROUND TO BEDROCK. RAISED STONE MOUND 2 FT. BASE TO CAP. MARKED NEW BEARING TREES: A 9" DOUGLAS FIR BEARS N.20°W., 5.8 FT., SCRIBED "N 1/16 519 BT"; A 10" DOUGLAS FIR BEARS 5.83°E., 16.4 FT., SCRIBED "N1/16 520 BT". MOVED WORKING CORNER STONES TO CAP. MARKED CAP AS PER DIA GRAM. NAILED BRASS WASHER STAMPED "LS 1026" IN LOWER BLAZE AND PAINTED 6" WIDE RED BAND AND BOTH BLAZES RED ON BEARING TREES. BEARINGS TO BT'S BY COMPASS USING DECLINATION OF 20° EAST ~ DISTANCES MEASURED TO CENTER OF TREE. B.3 P.49.

MALHEUR NATIONAL FOREST TWO BIT CADASTRAL SURVEY

CONTRACT NO. 53-04H1-1-8441 N PRAIRIE CITY RANGER DISTRICT

SURVEY OF SECTION 16 EXTERIOR

AND WEST LINE OF SECTION 20,

TOWNSHIP 13 SOUTH, RANGE 35 EAST,

WILLAMETTE MERIDIAN,

GRANT COUNTY, OREGON

W.O.81-328B

LEGEND

SET CORNER MONUMENT, REMONUMENTED OR MONUMENTED DURING THIS SURVEY, BEING A 21/2"O.D. ALUMINUM PIPE 30" LONG WITH 31/4" ALUMINUM CAP WITH MAGNETIC BOTTOM. A CERTIFIED RECORD OF LAND CORNER MONUMENTATION FOR ALL G.L.O. 1/4 AND SECTION CORNERS TO BE FILED CONCURRENTLY WITH THIS MAP. NONE OF THESE CORNERS HAVE BEEN PREVIOUSLY RE-ESTABLISHED IN RECORDS OF GRANT COUNTY SURVEYOR.

SET CORNER MONUMENT DURING THIS SURVEY BEING A 21/2"O.D.
ALUMINUM PIPE 30" LONG WITH 31/4" ALUMINUM CAP WITH MAGNETIC BOTTOM. A COMPLETE DESCRIPTION OF CORNER ESTABLISHMENT APPEARS ON THIS MAP. THIS CORNER HAS NOT BEEN PREVIOUSLY ESTABLISHED IN RECORDS OF GRANT COUNTY SURVEYOR.

INDICATES U.S.F.S. PROPERTY BOUNDARY POSTED UNDER THIS CON-TRACT WITH 5 112 FOOT STEEL FENCE POSTS WITH U.S.F.S. PROPERTY BOUNDARY SIGNS ATTACHED.

L.O. GENERAL LAND OFFICE RECORD SURVEY INFORMATION.

CORNER MONUMENT NOTE NUMBER.

BT BEARING TREE.

WSV.5. WITH VISIBLE SCRIBING.

B. P. FIELD BOOK AND PAGE NUMBERS.

GENERAL SURVEY NOTES

1. EQUIVALENT DISTANCE IN METERS FOR SURVEYED LINES OBTAINED BY MULTIPLYING DISTANCE IN FEET BY CONVERSION FACTOR OF 1200÷3937 OR ONE SURVEY FOOT EQUALS 0.3048006096 METERS.

2. SURVEY FIELD NOTES ARE ON FILE IN THE OFFICE OF ARMSTRONG

2. SURVEY FIELD NOTES ARE ON FILE IN THE OFFICE OF ARMSTRONG SURVEYING & ENGINEERING, INC., 378 EAST SECOND STREET, PRINE-VILLE, OREGON ~ FOUR BOOKS.

3. BEARINGS FOR THE WEST LINE OF SECTION 20 OF THIS SURVEY ARE BASED ON SOLAR OBSERVATION TAKEN AT WEST 114 CORNER SECTION 20.

4. BEARINGS FOR THE SECTION 16 EXTERIOR LINES OF THIS SURVEY ARE BASED ON SOLAR OBSERVATION TAKEN AT NORTHWEST CORNER OF

SECTION 16.

5. GENERAL LAND OFFICE RECORD FOR TOWNSHIP SUBDIVISIONAL LINES
FROM OFFICIAL NOTES AND PLAT BY BAMFORD ROBB UNDER JOINT

G.L.O. CONTRACT NO. 383 WITH ROBB AND GRADON BEARING DATE MARCH 26, 1881. 6. BEARINGS TO BEARING TREES BY COMPASS USING DECLINATION NOTED ON RECORD MONUMENTATION SHEET.

SURVEYOR'S CERTIFICATION

I, DAVID B. ARMSTRONG, REGISTERED PROFESSIONAL LAND SURVEYOR NO. 1026 IN THE STATE OF OREGON, DO HEREBY CERTIFY THAT THIS PLAT AND THE NOTES HEREON AND SOR ATTACHED ARE A CORRECT REPRESENTATION OF A SURVEY I PERFORMED DURING SEPTEMBER, 1981, FOR THE UNITED STATES FOREST SERVICE, IN ACCORDANCE WITH THE STATUTES OF THE STATE OF OREGON AND THE ARTICLES OF CONTRACT NO. 53-04H1-1-8441 N WITH ARMSTRONG SURVEYING & ENGINEERING, INC., AN OREGON CORPORATION, PRINEVILLE, OREGON.

SEE ATTACHED SURVEY NARRATIVE.

SHEET 1 OF 14



RECORDATION

OFFICE OF COUNTY SURVEYOR, COUNTY OF GRANT, STATE OF OREGON.

I HEREBY CERTIFY THAT THE WITHIN INSTRUMENT WAS FILED FOR RECORD ON THE ______, 1981.

Robert W. Bagett GRANT COUNTY SURVEYOR