



**BASIS OF BEARINGS**  
SOLAR OBSERVATION

- LEGEND**
- Found monument as shown
  - Found 5/8" iron pin, unless otherwise shown
  - Set 5/8" x 30" iron pin with attached yellow plastic cap marked B-G-A SURVEY MARKER
  - ✕ Set rail road spike
  - ( ) Record bearing and distance
  - MOS: Record map of survey

NOTE: The bearings and distances shown to the rail road spike at approximate station 7+75 are to the true corner position, not to the found rail road spike. The found rail road spike is tied from the true corner position as shown.

SHEET 4 OF 4

RECEIVED AND  
FILED  
MAY 21 1986  
OFFICE OF COUNTY SURVEYOR  
Attest: *James E. Lawrence*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Robert D. Baggett*  
OREGON  
JULY 12, 1983  
ROBERT D. BAGGETT  
598

BAGETT - GRIFFITH & ASSOCIATES John Day, Oregon		
MAP OF SURVEY OF A PORTION OF THE RIGHT OF WAY LINES OF STATE HIGHWAY 26 & 395 SITUATED IN SECTIONS 22, 23, & 26, T13S, R31E, W.M.		
GRANT COUNTY, OREGON		
SURVEYED FOR	OREGON STATE HIGHWAY DEPARTMENT	
SURVEYED BY	R.D.B. & J.L.W.	Jan-Apr. '86
Scale: 1"= 50'	Drawn by: J.L.W.	April '86

RECORD MAP OF SURVEY NO. 932