being 6583.08 feet North & 1286.20 feet East of the SW corner of section 9, T16S, R30E, W.M.. Spring Point being 1378.57 feet North & 5664.96 feet East of the SW corner of section 9, T16S, R30E, W.M.. Said corner is monumented with an alum. pipe and cap. NARRATIVE: This survey was performed at the request of Bernard Bentz. The purpose of the survey was to create a dividing line across the Bentz Ranch. A search was made of the available records pertaining to this survey. Field measurements were made to locate existing monuments. New monuments were set at locations approved by Mr. Bentz.

The northern line of this survey generally follows along an existing fence line.

Due to extensive section corner obliteration in this area, I tied this survey to the southwest corner of section 9 which was monumented in 1981 by Carl Sundet, O.P.L.S. 1664. This section corner is remonumented with a 2-1/2" alum.

cap. See remonumentation records.
I found no unusual conditions with this survey.



BASIS OF BEARINGS

SOLAR OBSERVATION

LEGEND

Set 5/8" x 30" iron pin with attached yellow plastic cap marked B-G-A SURVEY MARKER

x ---- x Fence line

REFERENCES

Record Map of Survey No. 702

REGISTERED PROFESSIONAL LAND SHRVEYOR

OREGON
JULY 12, 1669
ROBERT D. BAGETT
598

BAGETT - GRIFFITH & ASSOCIATES John Day, Oregon

MAP OF SURVEY OF A LINE SITUATED IN THE SW 1/4 SEC. 4, NI/2NV2 SEC. 9, & WV2WI/2 SEC. 10, TI65, R30E, W.M.

GRANT COUNTY, OREGON SURVEYED FOR BERNARD BENTZ SURVEYED BY R.D.B. & J.L.W. & M.D.B. 8/6/86 Scale: /"=500" Drawn by: J.L.W. 8/8/86