

Point being 3160.01ft. North and 2863.53 ft. East of the SW corner of Sec. 12, T9S, R27E, W.M. which is monumented with a Grant County Surveyor iron pipe and brass cap.

BASIS OF BEARINGS SOLAR OBSERVATION

LEGEND

- Found 5/8" iron pin of record
- O. Set 5/8"x30" iron pin with plastic cap marked B-G-A SURVEY MARKER
- x Fence
 () Record bearing and distance

REFERENCES

Map of Survey No.s 239, 434, 546, 631

Deed Records	121	Page 578
	121 120	537 595
	124	407

NARRATIVE: This survey was performed at the request of Frank Horner to divide his property into two parcels as shown hereon.

A search was made of the available records pertaining to this survey. Field measurements were made to locate existing monuments. New monuments were set at locations indicated by Mr. Horner.

The only unusual condition I found was that the described line along the North boundary of tract I and the North portion of the West boundary of tract 2 as described in deeds does not exactly coincide with the existing fence line by a few feet.



APR 3 0 1987





	1	
BAGE	TT - GRIFFITH & ASS John Day, Oregon	SOCIATES
	MAP OF SURVEY	
OF DIVIDING LINE CREATING 2 PARCELS IN THE		
WI/2, THE SWI/4NEI/4 AND THE SEI/4 OF		
SEC. 12, T9S, R27E, W.M.		
GRANT COUNTY, OREGON		
SURVEYED FOR	FRANK HORNER	
SURVEYED BY	R.D.B., D.I.G. & M.W.P.	4/3/87
Scale: /"=200'	Drawn by: M.W.P.	4/18/87

RECORD MAP OF SURVEY NO. 988