

SURVEYS

<i>MAPS OF SURVEY</i>	<i>DEED RECORDS</i>
226	Misc. Book 6, Page 144
319	Book 42, Page 300
600	Book 122, Page 743
1050	Book 132, Page 817
1520	Inst. No. 991415
	Inst. No. 992243
	Inst. No. 992244
	Inst. No. 202771
	Inst. No. 210837
	Inst. No. 20050098
	Inst. No. 20071677

OREGON
JULY 13, 1999
KENNETH H. DELANO JR.
49865
RENEWAL DATE:
01/01/2012

KENNETH H. DELANE JR., PLS

- Found Aluminum capped monument set by Doug Ferguson in 1988. See Grant County Map of Survey No. 1050
- ◆ Found Brass capped monument set by Vernon Glaze. See Page 86, Surveyors Book 1.
- ◎ Found Iron pln. See Size & Map of Survey (MDS #) reference at symbol.
- Set 5/8"x30" rebar pln with yellow plastic cap marked "FS & E"
- ☒ Cal. Point, No Monument Set

(Bearing/Dist) Record Bearing/Dist returned
by Vernon Glaze, Book 1, Page 86

(Bearing/Dist) Record Bearing/Dist from Grant
County Map of Survey No. 226

[Bearing/Dist] Record Bearing/Dist from Grant
County Map of Survey No. 600

Bearing/Dist Record Bearing/Dist from Grant
County Map of Survey No. 1050

<Bearing/Dist> Record Bearing/Dist from Grant
County Map of Survey No. 1520

*BASIS OF BEARING: The North line of
the SW1/4 of Section 1 as shown
on Grant County Map of Survey 1050*

T13S R26E

LINE TABLE		
NUMBER	DIRECTION	DISTANCE
L1	S51°41'24"E	168.72
L2	S08°27'02"E	251.43

NUMBER	DELTA ANGLE	RADIUS	ARC LENGTH	CURVE DIRECTION	CHORD LENGTH
C1(CL)	06°56'53"	85.00	10.31	N83°21'10"W	10.30
C2(CL)	35°08'12"	335.00	203.44	N69°15'30"W	202.24
C3(CL)	43°14'22"	300.00	226.40	N30°04'13"W	221.07
C4	08°56'50"	70.00	10.93	S82°21'12"E	10.92
C5	35°08'13"	350.00	214.64	S69°15'30"E	211.29
C6	30°19'15"	315.00	166.70	S36°31'46"E	164.76

(CL) Indicates curve along the centerline of the easement.