

SITUATED IN THE SE1/4 SEC. 20 AND IN THE W1/2NE1/4 AND THE
N1/2NW1/4 SEC. 28, AND IN SEC. 29, T12S, R26E, W.M.
GRANT COUNTY, OREGON

SCALE 1" = 100'

RECORD MAP OF SURVEY NO. 826
AS SHOWN

- FOUND 1 1/4" IRON PIPE WITH ATTACHED BRASS CAP MARKED 1/4 IN EACH QUADRANT.
(SEE RECORD MAP OF SURVEY NO. 826).
- FOUND 2 1/2" ALUM. PIPE WITH ATTACHED NATIONAL PARK SERVICE ALUM. CAP SET IN CONC.
(SEE RECORD MAP OF SURVEY NO. 826).
- FOUND 1/2" IRON PIN WITH ATTACHED YELLOW PLASTIC CAP MARKED "BGA MARKER".
(SEE RECORD MAP OF SURVEY NO. 826).
- SET 5/8"x30" IRON PIN WITH ATTACHED YELLOW PLASTIC CAP MARKED "BGB SURVEY MARKER".

() RECORD BEARING AND DISTANCE.
(SEE RECORD MAP OF SURVEY NO. 826).

RECORD MAP OF SURVEY NO. 826.

DEED RECORD BOOK 76 PAGE 83

94	551
108	608-609
113	341-347
118	609
125	75-77
125	150-158

DEED INSTRUMENT NO. 960943

Robert D. Baggett

OREGON
JULY 12, 1963
ROBERT D. BAGETT
598

Renewal Date 12/31/97

THIS SURVEY WAS PERFORMED AT THE REQUEST OF WAYNE HILL OF THE NATIONAL PARK SERVICE, ACTING IN BEHALF OF LILLIAN MASCALL. THE PURPOSE OF THIS SURVEY WAS TO CREATE PARCELS 1 AND 2 OF THIS LAND PARTITION AND TO SET MONUMENTS AT CORNERS OF PARCEL 1.

A SEARCH WAS MADE OF THE AVAILABLE RECORDS PERTAINING TO THIS SURVEY. FIELD MEASUREMENTS WERE MADE TO LOCATE THE CONTROLLING MONUMENTS OF RECORD SURVEY NO. 826, WHICH FORM A PORTION OF THE BOUNDARY OF PARCEL 1. WE ALSO TIED THE SOUTH 1/4 CORNER OF SECTION 29.

THE NEW MONUMENTS WERE SET AT POSITIONS APPROVED BY MRS. MASCALL AND MR. HILL, AS SHOWN HEREON.

(N81°27'49"E 615.00)
N81°27'49"E 615.00

5.34 ACRES
(5.09 ACRES EXCLUDING
ROAD RIGHT OF WAY
IN DEED BOOK 113
PAGE 341-347)

S81°27'49"W 615.00
(S81°27'49"W 615.00)

PARCEL 2
UNSURVEYED

SHEET 2 OF 2