


CORNER RESTORATION

CORNER C 1/4, SECTION 35 TWP 10S RANGE 27E

ORIGINAL SURVEY BY: NA

CONTRACT NO:

CONTRACT DATE:



ORIGINAL DESCRIPTION
This corner not previously established.

RESTORATION BY, STAMP AND DATE
Kenneth H. Delano Jr., P.L.S.
Staff Surveyor
Ferguson Surveying & Engineering

Monument set on May 24, 2001

RECEIVED AND
FILED

July 3, 2001
OFFICE OF COUNTY SURVEYOR
Attest: *Donald H. Ferguson*



RENEWAL DATE 12/31/2001

EVIDENCE FOUND
This corner not previously established.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED:
Show how trees are scribed and basis of bearings, including compass var.

Set a 2-1/2" dia. x 30" aluminum pipe with a 3-1/4" dia aluminum cap stamped as shown in the "DIAGRAM", 26" in the ground mound of earth and stone.

From which:

A 8" Fir bears N80°W, 16.7 ft., scribed C1/4 S35 BT
A 6" Pine bears N 9°E, 50.2 ft., scribed C1/4 S35 BT
A 6" Fir bears N55°30'E, 10.8 ft., scribed C1/4 S35 BT
A 8" Pine bears S 1°E, 16.5 ft., scribed C1/4 S35 BT
All bts with Aluminum chaining nail.

DIAGRAM
T10S R27E
C 1/4
S35
2001
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with a Leica TCA 1600 Total Station.

SEE GRANT COUNTY MAP OF SURVEY NO. 1602