


CORNER RESTORATION

CORNER SE 1/16, SECTION 35 TWP 10S RANGE 27E

ORIGINAL SURVEY BY: NA

CONTRACT NO:

CONTRACT DATE:



ORIGINAL DESCRIPTION

This corner not previously established.

RESTORATION BY, STAMP AND DATE

Kenneth H. Delano Jr., P.L.S.

Staff Surveyor

Ferguson Surveying & Engineering

Monument set on May 24, 2001

**RECEIVED AND
FILED**

July 3, 2001

OFFICE OF COUNTY SURVEYOR

Attest: *[Signature]*



RENEWAL DATE 12/31/2001

EVIDENCE FOUND

This corner not previously established.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED:

Show how trees are scribed and basis of bearings, including compass var.

Set a 5/8" dia. x 30" iron pin with a 2" dia aluminum cap stamped as shown in the "DIAGRAM", 26" in the ground

From which:

A 8" Pine bears S16°W, 39.2 ft., scribed SE1/16 S35 BT
A 12" Pine bears N42°W, 3.8 ft., scribed SE1/16 S35 BT
All bts with Aluminum chaining nail.

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with a Leica TCA 1600 Total Station.

SEE GRANT COUNTY MAP OF SURVEY NO. 1602

DIAGRAM
T10S R27E
SE 1/16
S35
PLS 49865