


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-20

**History of original corner establishment:**

Grant County Survey Records show no previous establishment of this Cor.

In 1955, Martin Louther established the approx. 1/16 Cor. and set an iron pin as a monument marking the corner. This work is not on file in the Grant County Surveyors Office. The notes pertaining to this were obtained from Mr. Louther By Elmo Calkins of the U.S Forest Service.



**Description of corner evidence found:**

Grant County Survey Records show no previous establishment of this corner.

Found 5/8" iron pin, as established by Martin Louther in 1955, for the approx. C-E 1/16.

The above described iron pin Bears N30°42'W., 17.04 ft. from the C-E 1/16, as established by this survey.

**Description of monument and accessories | established to perpetuate the original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 22" in the ground.  
From Which.  
A Pine 6" dia., Bears N43°W., 14.3 ft., scribed: C-E 1/16 S23 BT  
A Pine 10" dia., Bears S15°E., 12.4 ft., scribed: C-E 1/16 S23 BT  
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.  
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & South 6 ft. from the corner.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

**OREGON**  
JULY 12, 1968  
**DOUGLAS M. FERGUSON**  
848

This work is performed by:  
Douglas M. Ferguson PLS 848  
Mt. Vernon Oregon.  
On: Sept. 9, 1985  
Refer to Map of Survey No. 920

Office of Sumner County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 29 day of June, 1986  
Robert D. Banta by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)