

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. A-13

History of original corner establishment:

Corner was originally established by
W.H. Byars, in Sept., 1873, under
General Land Office Contract No. 197.
Surveyor Generals Notes State:
Set a Volcanic Stone 14x8x7 for the
corner to Sections 3,4,33 & 34.

DIAGRAM

T9S R29E
S33!S34
-.-
S 41S 3
T10S
1986
PLS 848

Description of corner evidence found:

Found 14"x8"x7" stone with 3 grooves on East & West
faces, set in the bottom of a muddy water course.

No accessories were originally established.
Since the above described stone does not look like it
has been moved (the water course is on a gentle grade
and would not have been moved by water) it is accepted
as the Section Corner position.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 24" in the ground & set original stone South
alongside pipe.

From Which:

Set 5/8" x 30" iron pins, with plastic caps stamped SURVEY MARKER PLS 848, &
steel guard posts, with Bearing Tree and Warning signs, as follows:
N45°W., 20.0 ft., N45°E., 13.0 ft., S45°E., 20.00 ft., &
S45°W., 14.0 ft.,

Measurements to accessories taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: April 14, 1986
Refer to Map of Survey No. 931

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*30* day of.....*June*....., 19.....*86*
.....*Douglas M. Ferguson*..... by.....
(COUNTY OFFICIAL) (DEPUTY)